



Infinite
Peripherals®

LINEA PRO® 6

General Specifications

Mobilize Your Enterprise™

The phenom. The latest sensation from Apple works wonders with our next-generation Linea Pro. For Apple® iPhone® 6.

**Headquarters/
Main Warehouse**
2312 Touhy Avenue
Elk Grove Village, IL 60007

Office (847) 818-1260
Fax (847) 818-1287
Toll-Free (800) 278-7860
Email info@ipcprint.com

**Mobility Sales/
Technical Support Center**
1641 McGaw Avenue
Irvine, CA 92614

Office (949) 222-0300
Fax (949) 222-0375
Toll-Free (866) 278-7860
Email info@ipcprint.com

Standard Features



2D Scanner



Li-ion
Battery



Lightning™
Connector



Magnetic
Stripe Reader



1D Scanner



Encryption
Capable



RFID



Bluetooth®

Optional Features



Made for
iPhone

ipcprint.com

©2015 Infinite Peripherals, Inc.



Infinite
Peripherals®

LINEA PRO 6

FEATURES

Standard Features	2D high speed imager, Li-ion battery, Lightning Connector, Mag-stripe Reader
Optional Features	1D Barcode Reader, Encryption Capable MSR, RFID, Bluetooth

MECHANICAL

Compatibility	iPhone 6
Dimensions (LxWxH)	1D Scanner: 157mm x 77mm x 22mm (6.2" x 3" x .9") 2D Scanner: 157mm x 77mm x 27mm (6.2" x 3" x 1.1")
Weight	147 grams (5.2 oz.) without iOS device
Port	Mini USB for device charge and sync

ELECTRICAL

Barcode Scanner	1D laser or 2D high speed imager (supports all major 1D or 2D barcodes)
Battery Capacity	Rechargeable Li-ion battery 3.7V / 2040mAh
Battery Life	Over 10,000 scans and swipes per full charge
Card Reader	3-track bidirectional Magnetic Stripe Reader (MSR)
Contactless: RFID (Optional)	ISO/IEC 14443 Type A & B, MIFARE, supports major NFC/contactless schemes

Encryption & Key Management (Optional)

3DES-112, AES 128/256, DUKPT

Bluetooth (Optional)

Bluetooth 2.0 compatible, Class 2, Serial Port Profile (SPP)

Indicator

Visual: 4 LEDs for battery status
Audio: Electromagnetic buzzer

CERTIFICATIONS

Certifications	Apple MFi, PCI PTS 3.x SRED (optional)
----------------	--

ENVIRONMENT

Operating Environment	Temperature: 0°C to +40°C (32°F to +104°F) Humidity: 5% to 90% RH
Storage Environment	Temperature: -10°C to +50°C (14°F to +122°F) Humidity: 5% to 90% RH

Specifications subject to change without notice.
Apple, iPhone, and Lightning are trademarks of Apple, Inc., registered in the U.S. and other countries.
The Bluetooth® logo is a registered trademark owned by Bluetooth SIG, Inc.