

RacMAX Series AC Protection

RM2600—RACK MOUNTABLE SURGE PROTECTOR



Features

- Eight protected AC power outlets
- Protect or Disconnect Circuitry
- Front panel circuit breaker
- Power indication light
- Single-height rack mountable chassis (1U)
- 10-foot power cord

Technical Specifications

Designs and specifications are subject to change without notice due to product improvement.

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	Yes (1)
Grounding Requirements	Uses Electrical Ground
	#10 AWG for Primary
	#14 AWG for Isolated Loop
Recommended Ground Impedance	< 0.5 Ohm
Width	19"
Height	1.75" (1U)
Depth	4.5"
Weight	5.17 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	N/A

For up-to-date
warranty information
see our web site:
www.itwlinx.com



AC SURGE PROTECTION:

SurgeGate Plus Circuitry	N/A
Protect or Disconnect Circuitry	Yes
Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Over/Undervoltage Voltage Protection	N/A
Overvoltage Voltage Shutoff	N/A
Undervoltage Voltage Shutoff	N/A
Single Pulse Energy Dissipation	1350 Joules
Peak Impulse Current	32,000A
EMI/RFI Noise Filtration	50db (99.7%)
Line Voltage	120VAC, 50/60Hz
Initial Clamping Level	200V Peak, 141 Rms
UL 1449 Rating	330V
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1–5 Nanoseconds
Plug Configuration	Straight
Number of Outlets	8 (rear)
Switched Outlets	All eight
Cord Length	10 ft

SIGNAL LINE SURGE PROTECTION:

TELCO CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resetable	N/A
Clamping Level	N/A
Response Time	N/A
Capacitance	N/A
Suppression Modes	N/A
Wires Protected	N/A
Termination Type	N/A

COAX CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resetable	N/A
Response Time	N/A
Termination	N/A
Antenna/Cable Lines Protected	N/A
Antenna/Cable Clamping Level	N/A
Antenna/Cable Attenuation	N/A
Satellite Lines Protected	N/A
Satellite Clamping Level	N/A
Satellite Attenuation	N/A

LAN CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resetable	N/A
Performance Rating	N/A
Clamping Level	N/A
Response Time	N/A
Wires Protected	N/A
Termination Type	N/A

Applications:

- Telephone Systems
- Workstations
- Printers
- Fax Machines
- Copiers
- TVs / VCRs
- Cameras
- Access Controls
- Alarms

Ordering Information

ITW Linx Part Number	Description
GRM0600	8-outlet Rack-mountable AC surge protector, with Protect or Disconnect circuitry. Fits standard 19" Racks / Cabinets.