

# Lane/8000

# An enhanced, secure, sleek and smart checkout experience

- Engage consumers with an extra large multimedia touchscreen and user-friendly interface
- Improve checkout experience with quick and easy payment options
- Integrate it easily into any environment
- Help reduce PCI-DSS audit scope with seamless semi-integrated configuration options
- Increase payment security with a PCI PTS
   5.x certified device



















Designed for speed and efficiency, the Lane/8000 creates new points of consumer engagement that improve brand loyalty and drive additional sales.

### Future-proof payment security

PCI PTS 5.x certified, the Lane/8000 is designed to ensure long-term compliance. It uses the latest cryptographic schemes with future-proof encryption and additional anti-theft systems, such as Kensington locks.

# Support for all payment options

The Lane/8000 supports EMV chip & PIN, EMV chip & sign, magstripe transactions and the broadest range of contactless/NFC, mobile wallet, and alternative payment methods. Each payment method is highlighted via illumination for easy and convenient use.

# Consumer-friendly design enabling greater customer engagement

An intuitive, interactive device, the Lane/8000 transforms the point of sale into a point of engagement. It offers the same user experience, touchscreen capabilities, and user-friendly interface as a tablet. Multimedia support is also available along with Bluetooth LE.

### Lower total cost of ownership

Support for semi-integrated configurations simplifies compliance with the latest PCI DSS security standards while minimizing your compliance costs.

## Industry-proven and reliable technology

Backed by over 35 years of development experience, the Telium TETRA operating system is the perfect combination of payment expertise and webbased design creativity. It offers powerful security mechanisms to protect







NAME			Lane/8000
Processor	Crypto and applications processor	Cortex A5, 64 bits	•
Memory	Internal Optional	512 MB Flash, 512 MB RAM Micro SD up to 32 GB	• Optional
OS		Telium TETRA	•
SAM		3	Optional
Card Reader(s)	Magstripe (dual head) Smart card contactless Smart card contact	ISO1/2/3, 500K reads lifespan EMV Level 1 EMV Level 1 compliant, 500k reads lifespan	•
Display	Color	7' backlight WVGA, TN* display (800x480)	•
Touchscreen	Capacitive	Finger & stylus (1 million signature lifespan)	•
Stylus	Passive	Tethered included	•
Keypad		15 keys, raised markings, backlit ADA friendly	•
Audio	Buzzer Audio jack Speaker	Stereo Mono	Optional Optional
Terminal Connectivity	Wired Wireless	Ethernet 10/100 base T Ethernet switch WIFI and Bluetooth (including BLE)	Optional Optional
Terminal Connections	USB Serial Powered USB Powered RS 232 Powered Ethernet External power supply	USB Host USB Slave 1 RS232 12 V (USB retail) 12 V POE Compliant with 802.3af (1)	Optional Optional
Stand Mounting		Universal Payment Mount	Optional
Terminal Size		7.87" x 8.07" x 1.73" (200 x 205,5 x 44 mm)	•
Weight		28.08oz (796g)	•
Environment	Operating temperature Storage temperature Relative humidity	32°F to 122°F (0 to +50°C) -4°F to 131°F (-20 to +70°C) 85% HR at 104°F (+40°C)	•
Security	PCI PTS Anti-theft	PCI PTS 5.x certified Kensington lock receptacles Secure mounts available	• Optional





<sup>\*</sup> TN: Twisted Nematics
\*\* This locally compliant pinshield is not PCI certified, it is used where local regulations overruled PCI