## MARATHON TIELD COMPUTER

OUR BREAKTHROUGH FORM FACTOR HELPS RESOLVE ISSUES IN REAL-TIME, ON THE FLOOR.







Today's supply chain is a nonstop series of challenges, and a nonstop quest for efficiencies. The Marathon Field Computer aids supervisors and QC personnel in warehousing, distribution, and manufacturing, by giving them the computing power they need in a highly mobile package.

Take the case of the warehouse supervisor who needs to address an exception on the floor. He undocks his Marathon Field Computer from its Smart Desk Dock, where it is connected to an external monitor and mouse, just like his old laptop, and heads down to the floor. But unlike his large laptop, the Marathon's ergonomics allows easy operation as he takes notes standing up using both the full QWERTY keyboard and touchscreen. When he sees damaged goods on a pallet, the integrated 2MP camera lets him pause to take a quick picture for later reference. As he arrives at the aisle where the associate has a question, the supervisor receives an instant message via software installed on the Marathon's Windows XP or Windows 7 OS. He replies to the IM, answers the associate's question, and returns to his office - never disconnected, never out of reach, and always in control.

Learn more today at lxe.com/marathon.





IP 65 DESIGN



**BIOMETRIC MOUSE** 



OUTDOOR DISPLAY



HIGH RES CAMERA



4' DROP



**SMARTDOCK** 



#### **SPEED**

Intel® Atom Z530 1.6GHz Processor with up to 2GB RAM

#### **SECURITY**

Integrated fingerprint-reader mousepad

#### **INDUSTRIAL DESIGN**

IP 65-rated with up to 4' drop to concrete & MIL-STD-810F vibration rated

#### CONNECTIVITY

802.11a/b/g/n & GPS

#### **VERSATILITY**

Full QWERTY keypad, touchscreen, optional mag stripe reader, 2D imager, voice-ready, with 2 high-speed USB ports, adapt the Marathon for wide variety of field service and mobile workforce applications

**LXE** | Mobile Computers

# MARATHON\* TECHNICAL SPECIFICATIONS







#### **PLATFORM**

#### **Processing & Memory**

- Intel® Atom Z530 1.6GHz
- 1GB or 2GB DDR2 SDRAM

#### System

- Windows® XP Pro
- Windows® 7 Pro
- Windows® Embedded Standard (WES 2009)
- Available recovery DVD with hardware drivers

#### **Display & Touch Screen**

- 7" (18 cm) WVGA (800x480) display
- Standard 400 NIT indoor display
- Optional transflective indoor/outdoor display
- 4-wire resistive touchscreen

#### **Hard Drives**

 8GB, 16GB, 32GB & 64GB solid state drives

#### **Power Supply & UPS**

- Integrated Li-ION primary battery, 2.5-hr life
- Optional secondary batteries for 6- & 9-hr operation

#### **Enclosure**

- High-strength magnesium housing
- Weight: 2.2lb (0.99kg) w/ integrated battery
- Dimensions: 8.1"x78"x1.3" (206mm x 197mm x 33mm) w/ integrated battery

#### CONNECTIVITY

#### **Optional Software**

- Freefloat Terminal Emulator
- Freefloat Link\*One Barcode Wedge
- On-screen soft keyboard
- VoIP support

#### **Interfaces**

- Full QWERTY keyboard w/ number pad
  - backlit
  - 10 single touch function keys
- Biometric mouse
- Finger print reader
- 2 USB high-speed host ports
- Power for in-terminal charging
- Audio for headset
- Dual speakers w/ adjustable volume control

- Integrated microphone
- External docking connector
  - 2x USB high-speed host ports
  - External WWAN radio & GPS antenna ports
  - RS-232
  - GA expansion port
  - Power input for interminal charging
- LEDs
  - Radio status
  - Solid state disk drive status
  - Power status

#### **Radio Support**

- WLAN: 802.11 a/b/g/n
- WPA or WPA2 security
- Bluetooth® 2.1+EDR
- AGPS included
- Internal antennas

### **DATA CAPTURE**

#### Barcode

• Optional 2D imager

#### Camera

 2Mp color autofocus camera

#### **Magnetic Stripe Reader**

 Optional magnetic stripe reader

#### **ENVIRONMENTAL**

- Ingress Protection: IEC 60529 compliant to IP65 Design
- Drop: 4ft. (1.2m) multiple drops to concrete
- Operating temperature: -4° to +122°F (-20° to +50°C)
- Storage temperature: -22° to +140°F (-30° to +60°C)

#### **Approvals**

- Emissions: FCC & ETSI
- Immunity: ETSI

- Safety: UL 60950-1, CSA C22.2 No. 60950-1, EN 60950. IEC 60950
- Battery Safety: UL 2054, IEEE 1725
- Radio: FCC Part 15C, IC RSS210, 102, EN 300 328, China SRRC, Singapore IDA, Malaysia SIRIM
- Radio Safety: FCC OET Bulletin 65, IC RSS 102, EN 50360
- RoHS compliant

### **CUSTOMIZATIONS**

#### **Accessories**

- Desktop cradle
  - 2x USB high-speed host ports
  - Ethernet, RJ-45
  - VGA expansion port
  - Power input for interminal charging
- Vehicle cradle
  - 2x USB high-speed host ports
  - Ethernet, RJ-45
- External WWAN radio & GPS antenna ports

- RS-232
- VGA expansion port
- Power inout for interminal charging
- RAM mount support
- Carry solutions
  - Hand strap
  - Shoulder strap
  - Carry case

#### **Developers**

 Free SDK available: lxe.com/developer



Please visit lxe.com/marathon or scan left with your barcode-enabled device.



125Technology Parkway Norcross, GA 30092 1-800-664-4593 info@lxe.com











