





PRO PANEL 21.5-A | 635049

# Pro Panel 21.5"

Android All-in-One Touchscreen

# **FEATURES**

- + OS: Android 13 GMS
- + MTK G700 Processor
- + 21.5" 1920 x 1080 PCAP multi-touch screen
- + True-Flat PCAP multi-touch screen
- + Power Over Ethernet Enabled
- + IP55 Rated for Water and Dust Resistance (Front & Back)
- + Heat Resistance up to 140° F (60° C)

# All-in-One Touchscreen

The Pro Panel 21.5" Android All-in-One Touchscreen combines the rugged durability of our Kitchen Premium Series monitors with an integrated Android processor—making it the perfect terminal for kitchen display systems, customer kiosks, POS stations, digital signage, and more.

Enjoy full HD resolution on a slim, wide 21.5" LCD PCAP multi-touch screen that's IP55-rated (front and back) to withstand heat, grease, and humidity in the toughest environments. Plus, with Power over Ethernet (PoE) support, you can streamline your setup using a single USB-C connection for both power and data.

logiccontrols.com



# **Pro Panel 21.5-A Specifications**

#### **SYSTEM**

Motherboard: G17
Processor: MTK G700
Memory: 8GB LPDDR4X
Storage: 128GB eMMC

### DISPLAY

Size and Resolution: 21.5" 1920x1080

Touch Screen: True-Flat PCAP multi-touch

Brightness: 350 nits Backlight: 50,000 Hours

#### I/O PORTS

USB-Type A: 4 x USB 2.0;

USB-Type C: 1 x USB 3.0 (DP / PD 5V/2A, 12V/1A)

Serial Port: 1 x RJ-50 (10P10C)

LAN:: 1 x RJ-45 (802.3bt PoE++)

Power Button: 1

#### COMMUNICATION

WLAN+BT: 802.11ax, BT5.2

#### CERTIFICATE

EMC & Safety: FCC Class A, CE Mark, LVD IP Rating: IP55 Front and Back

#### **ENVIROMENTAL**

Operating temperature: 0°C ~ 35°C (32°F ~ 95°F) Storing temperature: -20°C ~ 60°C (-4°F ~ 140°F) Relative humidity: 20% ~ 85% RH non-condensing

#### **DIMENSIONS**

L x W x H: 535mm x 388.4mm x 46.6mm (21.1" x 15.3" x 18") Weight: 23 lbs. (5.9 kg)

## MOUNTING

VESA Mount: 100 x 100

**OS SUPPORTED** Android 13 GMS

