



- Automatic message scrolling and “smart scrolling”
- Command set and firmware downloadable options
- Choice of interface; USB or serial
- Better visibility due to optically matched lens and wider character pitch
- Available with emulation of many popular command sets, including OPOS/JPOS
- Adjustable viewing angles
- Available in beige and dark gray, 120V and 220V

LDX9000



LDX9000 SPECIFICATIONS

OPTICAL (FLUORESCENT DISPLAY)

Digits per row	20
Number of rows	2
Digit configuration	5x7 Dot Matrix
Digit Height	9.5mm
Digit Width	6.2mm
Digit Pitch	7.7mm
Character configuration	ASCII
Brightness	900 cd/m ² typical
Display color	Blue -green
MTBF	300,000 hours

ELECTRICAL

Input power (to adapter)	120VAC , 60Hz 220VAC, 50Hz (optional)
Output power (from adapter)	7.5VAC 1A
Connector	2 conductor female jack
Pole cable connector	10 - pin mini -DIN (female)
Interface cable	
Pole side connector	10 - pin mini -DIN (male)
Computer side connector	USB: Type A Serial: DB9 (female) Pass -thru: DB925 (male)
Power connector	2 conductor male jack

ENVIRONMENTAL

Operating temperature	0°C to 50°C
Relative humidity	85% max, non -condensing
Storage temperature	-20°C to 70°C
Relative humidity	90% max, non -condensing
Vibration (10 to 55Hz)	4G's
Shock	40G's

INTERFACE

USB	USB 2.0 standard
Serial	RS232
Baud rates	2400/4800/9600 */19200
Protocol	8 data bits, no parity, 1 stop bit
RTS/CTS are tied together in connector.	
DSR/DCD/DTR are tied together in connector.	
WiFi	IEEE 802.11 b/g/n
Bluetooth	Bluetooth 2.1

*default factory setting

MECHANICAL

Weight	2.7lbs (1.23Kg)
Dimensions (inches)	(width x height x depth)
Fluorescent display	8.50 x 3.37 x 1.75
Rectangular base	2.12 x 2.00 x 2.25
Base plate	4.0 x 0.09 x 8.0
Overall height (typical)	24 in

CONNECTOR PINOUT

USB Type -A connector

Pin #	Function
1	V+
2	D-
3	D+
4	Ground

Serial DB9 female connector

Pin #	Function
1	DCD
3	Data
4	DTR
5	Ground
6	DSR
7	RTS
8	CTS

Serial pass -thru DB25 female connector

Pin #	Function
2	Data
4	RTS
5	CTS
6	DSR
7	Ground
8	DCD
20	DTR

ORDERING INFORMATION

LDX9000	Serial
LDX9000 -PT	Serial pass -through
LDX9000UP	USB (port -powered)
LDX9000W	WiFi
LDX9000BT	Bluetooth
LDX9000X	Serial double sided display
LDX9000XU	USB double sided display (with ext. power adapter)