



Features

- Rewinder option
- Bicolor
- Velocity of 5 lines per second
- Easy paper roll replacement

MP200E

Impact Printer





MP200E SPECIFICATIONS

MECHANICAL

 Dimensions
 9.5in x 6in (24.32cm x 15.61cm)

 Weight
 5.24lbs (2.38kg)

Operating temperature 41°F to 104°F (5°C to 40°C)

Operating humidity 10 - 80%

Storage temperature -4°F to 140°F (-20°C to 60°C)

Storage humidity 5 - 95%

INTERFACES

Ethernet

PRINTING

MethodDot MatrixWidth2.5in (6.35cm)Velocity5 lines per secondFeeding velocity400 points per line/column

FEATURES

MCBF print head 120 million characters MCBF mechanism 18 million lines

FUNCTIONALITY

Cash drawer driven Paper cutter with partial or full cut Compatibility with ESC/POS commands

POWER

AC 110V/220V, 50-60Hz

PAPER ROLL

Type Paper roll auto copied or carbon copied Number of sheets Three (original plus two sheet copies)

Thickness 0.065 - 0.13mm per sheet

Width 2.9in (7.5cm)
Paper roll external diameter 3.14in (8.0cm)
Paper roll internal diameter 0.47in (1.2cm)

Type of ink ribbon ERC - 38 (black, purple, black /red)

DRIVERS

Driver Windows Printer Driver

(7, XP, 2000, 2003, Vista, 32 & 64 Bit, XP Embedded, inux, OPOS, WEPOS)

Compatible Epson, Samsung





bematechus.com sales@bematechus.com 516.248.0400