

## Features

- Flexible configuration available
- Easy to change or replace HDD
- Cable management compartment
- Supports a wide range of operating systems
- Easy access to system core for maintenance
- Optimal MSR and customer display (line display or LCD) available



# SB9015F

## Dual-Core All-in-One Terminal

SB9015F delivers the perfect blend of quality, performance and durability that you would expect from a best-in-class Point-of-Sale hardware. The economical price point with an industrial computer core and touch screen makes the SB9015F a perfect choice when an All-in-One solution is needed. Just one thumb screw located at the back panel of the monitor allows easy access to the computer core for service and maintenance.

# SB9015F SPECIFICATIONS

MODEL	SB9015F 15in All-in-One	
	SB9015F - D525	SB9015F - Core i3
SYSTEM		
CPU	Intel Atom Processor, D525, Dual-Core, 1.8GHz	Intel Processor i3 Dual-Core
Chipset	ICH8M chipset	HM65 express chipset
Memory	2 slots, DDR3 1066/1333, up to 4GB (standard 2GB)	2 slots, DDR31066/1333, up to 8GB
Graphics memory	Shared memory up to 224MB	
Storage	SATA 2.5in HDD (standard 320GB)	
Operating system	Windows 7 Pro, POSReady 7, POSReady 2009	
DISPLAY		
LCD panel	15in TFT LCD	
Resolution	1024 x 768	
Brightness	250cd/m²	
Touch screen	5-wire resistive touch (RS232 - COM2)	5-wire resistive touch (RS232 - COM5)
	Optional PCAP touch (USB)	
Tilting angle	0° to 90°	
I/O PORTS		
External DC input	1x DC jack (connected to power adapter)	
USB	6x USB 2.0	
Serial ports	3x DB9 (COM1/3/4), 1x RJ45 (COM5), all with DC5V/12V on pin 9 (jumper option)	3x DB9 (COM1/2/6), 1x RJ45 (COM4), all with DC5V/12V on pin 9 (jumper option)
VGA	1x DB15 2 video VGA connector	
LAN	1x RJ45, 10/100M/1Gbit	
Cash drawer port	1x RJ11, 12V/24V jumper selectable, COM port control	1x RJ11, 12V/24V jumper selectable, GPIO control
PS/2 port	1x PS/2 keyboard	
Parallel port	Optional 1x DB25 on cable	
Audio	1x audio out 2x 1W built-in speaker	
DC output	1x DC12V output	
ELECTRICAL		
External input	100V to 240VAC, 50 to 60Hz, 2.0A	
External output	DC 19 - 24V 5A	
Output power	120W max	
ENVIRONMENTAL		
Temperature	Operating: 34°F to 104°F (0°C to 40°C) Storage: -13°F to 158°F (-25°C to 70°C)	
Relative humidity	8% to 80% non-condensing	
MECHANICAL		
Dimensions (W x H x D)	13.7in x 13.0in x 8.4in (34.8cm 32.9cm x 21.3cm)	
Weight	22lbs. (10Kg)	
OPTIONAL ACCESSORIES		
Customer display (VFD or LCD), MSR Fingerprint reader, Wi-Fi		