



- True-flat bezel free 15in TFT LCD monitor
- Flexible configurations available
- Easy to change or replace HDD
- Cable management compartment
- Easy access to system core for maintenance
- Optional MSR and customer display (line display or LCD available)

SB9015T



bematechus.com



SB9015T SPECIFICATIONS

MODEL	SB9015T 15in True-flat All-in-One	
	SB9015T - D525 system	SB9015T - i3 system
SYSTEM		
CPU	Intel Atom Processor, D525, dual core, 1.8GHz processor	Intel i3-2310E 2.1GHz i3-3217U 1.8GHz dual core processor
System chipset	D525 + ICH8M chipset	HM65 chipset
BIOS	Phoenix Award BIOS	AMI 64Mbit UEFI BIOS
System memory	2 slots, DDR3 1066/1333, up to 4GB	2 slots, DDR3 1066/1333, up to 8GB
Graphics memory	Shared memory up to 224MB	
Storage	SATA 2.5in Hard Disk Drive (standard 320GB)	
DISPLAY		
LCD panel	15in TFT LCD	
Resolution	1024x768	
Brightness	250 cd/m²	
Touch screen	5-wire resistive touch (COM2)	5-wire resistive touch (COM5)
Tilting angle	0 to 90º	
I/O PORTS		
PS/2 port	1x PS/2 keyboard	
VGA	1x DB15 2 nd video VGA connector	
Serial ports	3x DB9 (COM1/3/4), 1x RJ45 (COM5), DC5V/12V jumper option on pin 9	3x DB9 (COM1/2/6), 1x RJ45 (COM4), DC5V/12V jumper option on pin 9
Ethernet	1x RJ45, 10/100/1000 Mbps	
USB	6x USB 2.0	
Audio port	1x audio out, 2x 1W built-in speakers	
Cash drawer port	1x RJ11, 12V/24V jumper selectable, COM port control	1x RJ11, 12V/24V jumper selectable, GPIO control
DC output	1x DC 12V output	
ELECTRICAL (External power adapter mounted inside system base)		
Input	96V to 264VAC, 50 to 60Hz 2.0A	
Output	DC 24V 5A	
Output power	120W max	
ENVIRONMENT		
Temperature	Operating: 34°F to 104°F (0°C to 40°C) / Storage: -13°F to 158°F (-25°C to 70°C)	
Relative humidity	8% to 80% non-condensing	
MECHANICAL		
Dimensions (HxWxD)	15.1in x 14.2in x 8.4in (384mm x 360mm x 213mm)	
Weight	22lbs (10Kg)	
OPTIONAL ACCESSORIES		
Customer display (VFD or LCD), MSR, Fingerprint reader, Wi-Fi		