![bematech by TOTVS logo]

Features

- True-flat, bezel-free and fanless design
- Slim, stylish and robust
- Rugged metal housing
- Double hinge height adjustment
- Folds flat for economical shipping
- Straightforward and easy to service in the field

SB9095

True-flat All-in-One Touch POS Terminal

The Bematech SB9095 All-in-One terminal packs great features, versatility and value into a sleek and neat design. It enhances the atmosphere of any business while providing excellent performance and reliability. With unique and easy detach design, the SB9095 minimizes use of screws and internal cable connections. The unit has options for integrated magnetic stripe reader, fingerprint reader, RFID/NFC reader and VFD/LCD customer displays.

bematechus.com

SB9095 SPECIFICATIONS

MAINBOARD

CPU	Intel® Celeron J1900 Quad-Core 2.0GHz
Memory	DDR3 SODIMM slots x2, up to 8GB RAM
Storage	SATA 2.5in (6.3cm) Hard Disk Drive / SSD / mSATA
OS compatibility	Windows 7 / POSReady / Windows 8 / Linux Kernel 2.6 or above

DISPLAY

LCD panel	15in LED-backlit display, XGA 1024 x 768
Touch screen	5-wire resistive touch, optional projected capacitive touch

I/O PORTS

USB ports	USB 2.0 x2, USB 3.0 x2
Serial ports	RJ45 x3
Ethernet	Gigabit, RJ45 x1
PS/2 port	PS/2 keyboard x1
Video port	VGA DB15 x1, HDMI x1
Cash drawer port	RJ12 x1 (dual cash drawer support)
Audio port	Line out x1

ELECTRICAL

Power supply	DC 24V 120W external power adapter
Input to power adapter	90 to 264VAC, 50/60Hz

ENVIRONMENTAL

Operating temperature	32°F to 104°F (0°C to 40°C)
Relative humidity	8% to 80%, non-condensing

MECHANICAL

Dimensions (W x H x D)	14.2in x 12.3in x 8.3in (36.1cm x 31.3cm x 21.0cm)
Dimensions folded flat (W x H x D)	14.2in x 4.2in 8.3in (36.1cm x 10.7cm x 21.0cm)
Weight	12.5lbs (5.7Kg)