

# xTablet Flex 10A with Android

#### The lightweight, rugged, entry level tablet with Android

The proven rugged Flex 10A is now available with next level Android 9.0 O/S performance, powered by the MT8163 Quad-Core Processor. GMS, SOTI and VMWare certifications offer the highest level of functionality, security and (OTA) management. Convenient features include an easy carry briefcase handle and back hand strap along with MobileDemand's versatile snap mount plate come standard. Optional keyboard and integrated MSR are also available for the Flex series. Extremely durable xCase, scratch-proof screen protector with ample storage and power make the Flex 10A with Andriod a perfect solution for light to medium-duty mobile applications and an ideal entry-level rugged tablet for construction, agriculture, distribution, and retail industries.

# Highlights

Rugged, lightweight form factor
Quick release mounting
Android 9.0 O/S
GMS, SOTI & VMWare Certified
Industry-leading value pricing
Keyboard option ready
Optional integrated Magstripe Reader
10.1″ display



## features

Android 9.0 O/S
GMS, SOTI & VMWare Certified
Rugged Lightweight Form Factor
Vehicle Mountable
Scratch-Resistant Screen Protector
Quad-Core Cortex-A53 Processor
Bluetooth 4.0

#### Accessories

Snap mount Briefcase handle Back hand strap Keyboard Integrated Magstripe Reader Stylus, tether and holder 2-point and 4-point shoulder straps

Warranty The xTablet Flex10A with Android comes with a 1-year warranty that covers hardware failure when the tablet has been used as designed.

### android



©2020 MobileDemand, LC MobileDemand and xTablet Flex 10A are trademarks. VERSION 09.30.20

Specifications		
DIMENSIONS	With case (excluding bumpers): 10.5" W x 7.2" H x .7" D (267mm W x 182mm H x 18.5mm D)	
WEIGHT	2.07 lb. (.94 kg) - base config	
DISPLAY	10.1" Capacitive 1280 (W) x 800 (H) IPS 250 NITS	
СРИ	MT8163 64-bit CPU, Quad-Core Cortex-A53, 1.3GHz	
MEMORY	3GB PCDDR3	
STORAGE	128GB	
O/S	Android 9.0 Pie	
EMM CERTIFICATION	SOTI VMWare	

SECURE PAYMENT

Powered by MAGTEK

RUGGEDIZED	MIL-STD 810G (5ft passed)
Screen Protector	Oleophobic, scratch-resistant glass
Operating Temp	14° F to +113° F (-10° C to 45° C)
Storage Temp	-4° F to +140° F (-20° C to 60° C)
Operating Humidity	5% - 95% non-condensing
CAMERA	Front - 2MP Rear - 5MP
I/O PORTS	Micro USB OTG USB 2.0 Mini HDMI Headphone DC Barrel Jack
AUDIO	$3W \times 1 @ 4\Omega$ , 2 integrated speakers
BUTTONS	Power; Volume +/-
SENSORS	Accelerometer
BATTERY SYSTEM	Lithium-ion polymer battery 22.2Wh, 6000mAh, 3.7V up to 4-6 hours <sup>1</sup> of battery life
WIRELESS/NETWO	RK
WLAN	WIFI 802.11 a/b/g/n
Bluetooth	4.0
AGENCY APPR	FCC-CE-IC



<sup>1</sup>Battery life varies significantly depending on settings, app usage, and other factors