

Motion® F5v PRODUCT SPECIFICATIONS



Processor/Cache	 Intel[®]
-----------------	---------------------------------------

Core™ i7 vPro™ Processor 1.2 GHz with Intel® Smart Cache (4MB of L3 cache, 2 Cores/4 Threads)

• Intel® Core™ i5 vPro™ Processor 1.06 GHz with Intel® Smart Cache (3MB of L3 cache, 2 Cores/4 Threads)

Operating System

• Genuine Windows® 7 Professional (32-bit)

Durability

• Meets MIL-STD-810G

IP54 rated

- Water, dust and splash resistant · Shock-mounted display and hard drive

Durable Gorilla™ glass

 Rubberized for shock dampening Magnesium-alloy internal frame Molded handle to prevent drops

Software

Display

· Motion Dashboard control panel

Motion/Softex OmniPass[™] Security software

 Windows Journal Sticky Notes

• Infineon Security Platform Tools · Pen enabled BIOS setup · Intel Mobile Clinical Assistant

Adobe Reader

Chipset • Intel® QM57

• 10.4" XGA TFT AFFS+ LED Backlight (1024 x 768) with durable Gorilla™ glass (standard)

 Optional View Anywhere® with durable Gorilla™ glass Intel Display Power Saving Technology (DPST)

Graphics • Intel® HD Graphics with dynamic frequency

Rotation: 0°, 90°, 270°

Video RAM Maximum 256MB total with Intel Dynamic Video

Memory Technology (DVMT)

Audio Controller • Intel® High Definition Audio

System Memory • DDR3 800MHz SDRAM memory

Base configuration of 1GB

· Upgradeable to maximum 4GB at point of purchase

System Storage

• 1.8" SATA Hard Disk Drive (HDD) with 160GB capacity

• Optional SATA Solid State Disk (SSD) with 64GB or 128GB

capacity

SATA 2.0 – 3.0 Gb/s

• AHCI

Integrated Communications

• WiFi® 802.11 a/b/g/n

Optional Integrated Mobile Broadband (Gobi[™] 2000)

with GPS capabilities

• Integrated Bluetooth® 2.1+EDR Module

Audio

Motion Speak Anywhere® noise cancellation technology

• Multi-directional array microphone design with 2 microphones

· Integrated speaker

I/O Ports

Docking connector

• USB 2.0 port located next to DC power-in port with

rubberized cover

Embedded I/O

• Optional 3.0 Megapixel camera (rear-facing)

• Optional 1.3 Megapixel front-facing web camera

• Optional 1D/2D Barcode Reader • Optional 13.56MHz RFID reader

Security

• Integrated Fingerprint Reader with OmniPass software

• TCG Trusted Platform Module (TPM) 1.2

· Smart card reader (optional) - ISO 7816 PC/SC - EMV2 2000 Level 1

• Computrace® Complete (optional)

Dimensions

• 10.0" x 10.0" x .95" (256mm x 256mm x 24.3mm)

Weight

• 3.3 lbs.1 (1.50 kg)

Battery

Battery life greater than 4 hours²

· Hot swappable Lithium Ion standard battery with 40WHr

capacity

Battery Charging

Time

Standard Battery - 1.5 hours (Tablet PC on/off)³

System Status

LÉDs

• Power on/off/stand by LED ring around power button

· Battery status LED on back

· Battery charge gauge on front

• RFID LED adjacent to RFID read trigger

AC Adapter

• 65W universal, 3-pin jack

• 100-240V 1.5a, 50-60Hz

Control Buttons

• One 5-way directional for navigation

• One function, one Dashboard and two programmable

Secure Attention Sequence (SAS)

 Camera capture RFID read trigger · Barcode scan trigger



Motion® F5v PRODUCT SPECIFICATIONS



Built-in Cameras	Rear-Facing Camera
Dunt-in Cameras	rtear-racing camera

Autofocus

- 3.0 megapixel resolution
- JPG photo format with a resolution up to 2048 x 1536 pixels
- · Illuminator light

Front-Facing Camera

- Autofocus
- Up to 1280 x 1024 resolution
- Webcam

Environmental

- Temperature
- Operation: +5°C to +40°C (41°F to 104°F)

 0°C to +40°C (32°F to 104°F) when configured with SSD storage

- Storage: -20°C to +60°C (-4°F to 140°F)
- Humidity
- Operating humidity: 8% to 80% without condensation
- Storage humidity: 8% to 90% without condensation
- Altitude
- Operation: Sea level 0 to 10K ft. sea level to 15K ft.
- when configured with SSD storage
- Storage: Sea level 0 to 15K ft.
- Enclosure class

Standards

ACPI 3.0b compliant

Safety

- AS/NZS 3260:1997
- AS/NZS 60950-1
- FCC/ANSI C63.41
- UL, CUL, CE (IEC/EN60950-1 A11/2004)
- CAN/CSA RSS-102
- FCC OET65 Supplement C
- ETSI EN 50392
- LVD (73/23/EEC)
- EU Directive 2002/95/EC
- EU Directive 2002/96/EC
- EU Directive 2006/66/EC and its amendments
- California Proposition 65
- Technical Instructions for Safe Transport of Dangerous Goods by Air (ICAO Doc #9284)
- Emergency Response Guidance for Aircraft incidents involving Dangerous Goods (ICAO Doc #9481)

Regulatory

- AS/NZS 3548:1995 Class B
 - AS/NZS 4771
 - AS/NZS 4268
 - AS/ACIF S042.1 (WCDMA/HSDPA)
 - AS/ACIF S042.3 (WCDMA/HSDPA)
 - · AS/ACIF S042.1 (GSM/EDGE)
 - AS/ACIF S042.3 (GSM/EDGE)
 - CAN/CSA ICES-003 Class B
 - CAN/CSA RSS-210 Issue 5
 - CAN/CSA RSS-132 (1xRTT/EVDO-0/EVDO-A)
 - CAN/CSA RSS-133 (1xRTT/EVDO-0/EVDO-A)
 - CENELEC EN 55022 Class B (CISPR22)
 - CENELEC EN 55024 (CISPR24)
 - CENELEC EN 61000-3-2
 - CENELEC EN 61000-3-3
 - ETSI EN 301-893
 - ETSI EN 300-328
 - ETSI EN 301-489-1
 - ETSI EN 301-489-3
 - ETSI EN 301-489-7
 - ETSI EN 301-489-17
 - ETSI EN 301-489-24
 - ETSI EN 300-330
 - ETSI EN 301-511
 - ETSI EN 301-908
 - FCC Part 15 Subpart B Class B
 - FCC Part 15 Subpart C (2.4Ghz)
 - FCC Part 15 Subpart E (5Ghz)
 - FCC Part 22 H (1xRTT/EVDO-0/EVDO-A)
 - FCC Part 24 E (1xRTT/EVD0-0/EVDO-A)
 - R&TTE (89/336/EEC) & R&TTE (99/5/EC)
- 3-year field-ready warranty

For more information and localized websites, please visit www.MotionComputing.com

1-866-682-2538

Warranty

© 2010 Motion Computing, Inc. All rights reserved. All product information is subject to change without notice. Motion Computing, Motion, Speak Anywhere and View Anywhere are registered trademarks of Motion Computing, Inc. in the United States and/or other countries. Microsoft Windows and Windows 7 are either registered trademarks of Microsoft Corporation in the United States and/or other countries. Intel, the Intel logo, Centrino, Intel Core and Core Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. BLUETOOTH is a registered trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Motion Computing, Inc. All other trademarks and registered trademarks or the property of their respective owners. 003-87-0264 Rev. A04-US/CA

¹Weight represents approximate system weight measured with a 40WHr battery. Actual system weight may vary depending on component and manufacturing variability.

² Battery life varies by configuration, applications in use, utilized features and operating conditions. Maximum battery capacity decreases with time and use. Motion battery life estimates based on MobileMark® 2007 performance testing.

³Approximate charging time. Validated charging from 5% to 90% with system on or system off.