

Essential performance. Enticingly priced.

NEC E SERIES

Large Screen LED-backlit LCD 32" | 42" | 46" | 55"



LED-Backlit, Commercial-Grade LCD Displays Ideal for Education, Corporate and Digital Signage Applications

The Essentials

With a brilliant panel and simplified controls, the NEC E Series delivers everything you need for captivating digital signage

- Integrated USB Player allows for playback of picture files
- High-definition and high contrast ratio displays provide stunning images
- Built-in tuner allows for high-definition broadcast capabilities
- Additional energy options include a Power Savings Mode to further reduce energy consumption

The Extras

Delivering more than just the basics, the NEC E Series has integrated features that will leave no head unturned

- LED backlighting enables eco-friendly digital signage
- Reduced bezel width creates seamless digital signage
- Multiple HDMI ports enhance best-in-class connectivity
- Internal, 10W down-firing stereo speakers enhance the experience with superior sound
- 3-year warranty protects your investment



Performance-Driven Design

The Essential

Quality design and performance is expected of digital signage displays in order to attract, engage and inform audiences. With a slim, sleek bezel and a high contrast panel, NEC E Series displays are points of attraction poised to deliver brilliant content.

The Extras

The NEC E Series goes above and beyond what you've come to know as a traditional display design. With an LED edge-lit backlighting source that contributes to a reduced depth and lighter weight, these displays are mere slivers of the previous generation of displays. These benefits also make this fourth generation of E Series displays easy to transport and install.




Corporate Applications

The Essential

Ideal for digital signage in corporate lobbies, and presentations, video conferencing and boardrooms, the NEC E Series allows for USB picture playback in concert with a brilliant display.

The Extras

LED backlighting enables a thinner, sleeker display – all the better to showcase corporate messaging and enable cross-company collaboration. LED backlighting also leads to reduced total cost of ownership and, with a mercury-free design, it has a reduced environmental impact as well.



Education Applications



The Essential

With integrated speakers and a tuner, the NEC E Series is designed for implementation in educational environments. Digital signage can achieve campus-wide connectivity through a single point of access by alerting passersby of upcoming events and emergency notifications, while classroom displays provide a bright alternative to projector screens.

The Extras

The NEC E Series is perfect for schools looking to upgrade their old CRT televisions. Impress prospective students, parents and visitors with a progressive, technology-forward school environment. What's more – these displays are priced to compete, meaning even schools with the tightest of budgets can upgrade their classrooms.

Eco-friendly Features

The Essential

Environmental features are an expected consideration when it comes to digital signage and the NEC E Series is no exception. An integrated backlight adjust setting allows users to customize the backlight strength, enabling a longer display life and lower power consumption. An energy savings picture mode is built into the on-screen menu to improve energy efficiency.

The Extras

With LED backlighting, the NEC E Series is more slim and sleek than ever. Not only are LED backlights mercury-free, they contribute to reduced power consumption and therefore a lower total cost of ownership.




Specifications

MODEL	E324	E424	E464	E554
LCD MODULE				
Panel Technology	A-MVA			
Viewable Image Size	32"	42"	46"	55"
Native Resolution	1360 x 768	1920 x 1080		
Brightness (Typical/Max)	350 cd/m²	360 cd/m²	350 cd/m²	
Contrast Ratio (Typical)	3000:1	1200:1	4000:1	
Viewing Angle	176° Vert., 176° Hor. (88U/88D/88L/88R) @ CR>10			
Aspect Ratio	16:9			
Active Screen Area (W x H)	27.5 x 15.4 in. / 697.7 x 392.2mm	36.9 x 20.9 in. / 938.2 x 531.3mm	40.4 x 22.9 in. / 1026.1 x 580.7mm	47.9 x 27.1 in. / 1217.2 x 687.8mm
Orientation	Landscape			
Displayable Colors	More than 16.7 million			
CONNECTIVITY				
PC/Mac Signal Compatibility	Yes			
Input Terminals				
Digital	HDMI (3)			
Analog	VGA 15-pin D-sub, RCA (Y, Cb/Pb, Cr/Pr) Component			
Audio	HDMI Audio, Stereo Mini-Jack			
External Control	RS-232C*			
Output Terminals				
Audio	SPDIF			
Audio Amplifier	10W (down-firing)			
POWER CONSUMPTION				
On (Typical)	45W	85W	100W	122W
ECO Mode Standby	<0.5W			
PHYSICAL SPECIFICATIONS				
Bezel Width (L/R, T/B)	0.39 in./0.39 in., 0.39 in./1.3 in. ; 9.9mm/9.9mm, 9.9mm/32.4mm	0.37 in./0.37 in., 0.37 in./1.3 in.; 9.5mm/9.5mm, 9.5mm/32.4mm	0.39 in./0.39 in., 0.39 in./1.3 in.; 9.9mm/9.9mm, 9.9mm/32.4mm	0.39 in./0.39 in., 0.39 in./1.3 in.; 9.9mm/9.9mm, 9.9mm/32.4mm
Net Dimensions (without stand; WxHxD)	28.6 x 17.4 x 2.5 in. / 725.7 x 442.8 x 62.8mm	37.7 x 22.6 x 2.5 in. / 957.6 x 574.0 x 63.5mm	41.2 x 24.5 x 2.5 in. / 1046.4 x 622.3 x 63.5mm	48.9 x 28.9 x 2.5 in. / 1242.1 x 734.1 x 63.5mm
Net Weight (without stand)	14.8 lbs. / 6.7 kg	26.7 lbs. / 12.1 kg	30 lbs. / 13.6 kg	44.2 lbs. / 20.1 kg
VESA Hole Configuration	100 x 100mm (4-hole)	400 x 400mm (4-hole)		
ENVIRONMENTAL CONDITIONS				
Operating Temperature	32-104°F / 0-40°C			
Operating Humidity	10 - 80%			
Operating Altitude	6562 ft. / 2000m			
LIMITED WARRANTY	3 years parts and labor, including backlight**			
ADDITIONAL FEATURES	Built-in NTSC/ATSC (8-VSP, Clear QAM) analog/digital tuner; Variable picture modes (Dynamic Standard/Energy Savings/Theater/Custom); Advanced Video/Audio Settings; Sleep Timer; Built-In closed captioning; Parental Control (V-Chip Function); Power management; USB Port			
SHIPS WITH	Power cord; VGA cable (Mini 15-pin D-sub); Wireless remote control; Batteries; CD-ROM (user manual); Stand; Stand Screws			
OPTIONAL ACCESSORIES				
NEC	External Single Board Computer (TNETPC-AF-WS); Wall Mount Kit (WMK-3257), Any OPS PC in combination with the OPS-DOCK			

* RS-232C communication is only unilateral. The displays will not send feedback commands.

** Warranty restrictions apply. Contact your representative for details.



For times when the remote is not available, full display controls are conveniently situated on the side of the bezel, allowing you to change channels, adjust the volume and access the on-screen display manager.

TileMatrix and TileComp are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.
©2015 NEC Display Solutions of America, Inc.
All rights reserved. rev. 1.27.2015

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE