

NLS-MT90

Model: MT9050-2WAM

Portable Data Collector

























Features

■ Superior Barcode Reading Performance

Armed with Newland's sixth-generation of **WIMG®** technology and its state-of-the-art 2D mega-pixel engine, the new NLS-MT90 can decode even poorer quality barcodes, such as soiled or wrinkled labels, with ease.

User-focused Ergonomics

The user-focused ergonomic design of the NLS-MT90 renders a lightweight and well-balanced device that reduces stress and fatigue during extended work sessions. Its ergonomically positioned side scan buttons provide the most comfort to use for either rightor left-handed operators.

■ Diverse Functionalities

Beyond the flexibility of its dual SIM card system, the NLS-MT90 offers Bluetooth/ dual band WiFi 2.4GHz and 5GHz / 4G/3G/GPS/GPRS/Camera/ NFC functionalities to meet various application needs.

Application Scenarios

■ Long-lasting Battery Life

The NLS-MT90 is equipped with a 4500mAh battery that provides a full-shift battery life of up to 10 hours from a single charge.

Heavily Customized Android

The value-added features of the NLS-MT90, including application protection and admin tool, seek to shore up Android's data security.

Industrial-grade Durability

The NLS-MT90's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.5m drops to concrete.

Current models released MT9050-2WAM (2D mega-pixel imager)



NLS-MT90

Portable Data Collector

SCANNING MADE SIMPLE

| Performance | Processor | 1.3GHz quad-core 64-bit processor |
|----------------------|-----------------------|--|
| | Operating System | Android 7.0 (64-bit) |
| | Memory | 2GB RAM, 16GB ROM |
| | Interface | Micro USB 2.0 OTG, Battery charging over USB supported |
| Physical | Dimensions | Maximum Size: 155(L) × 78.5(W) × 20.5(H)mm; Handheld Size: 155(L) × 76(W) × 18(H)mm |
| | Weight | 265g (including battery) |
| | Display | 5" (1280×720) capacitive touch screen |
| | Keypad | 10 keys (side keys included) |
| | Notification | Vibrator, speaker and multi-color LEDs |
| | Battery | 3.8V, 4500mAh |
| | Expected Battery Life | 10 hours |
| | Expected Charge Time | <5 hours (charge via AC adapter) |
| | Camera | 8 megapixels, auto focus, with LED flashlight |
| | GPS | GPS (AGPS), GLONASS |
| | Expansion | Micro SD card (max. 32GB) slot |
| | AC Adapter | Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz |
| Environmental | Operating Temperature | -20°C to 55°C (-4°F to 131°F) |
| | Storage Temperature | -30°C to 70°C (-22°F to 158°F) |
| | Humidity | 5% to 95% (non-condensing) |
| | Static Discharge | ±15 kV (air discharge), ±8 kV (direct discharge) |
| | Drop | 1.5m drops to concrete, 1.8m drops to concrete with rubber boot |
| | Sealing | IP65 |
| Barcode | Laser aiming | 1D: EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 39, Codabar, UCC/EAN128, RSS, ITF, |
| Scanning | Mega-pixel | ITF14, ITF6, ISSN, ISBN, Standard 25, Matrix 25, Industrial 25, Plessey, MSI Plessey, Code |
| | | 11, Code 93, etc. |
| | | 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec, |
| | | Chinese Sensible Code, Maxicode, Composite, etc. |
| RFID | 13.56MHz RFID | ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693 |
| Wireless | WLAN RADIO | IEEE 802.11 a/b/g/n, 2.4GHz and 5GHz |
| | WWAN RADIO | 2G: GSM/GPRS/EDGE (850/900/1800/1900MHz) |
| | | 3G: WCDMA (B2, B4, B5, B8) |
| | | 4G: TD-LTE (B38, B39, B40, B41) |
| | | FDD-LTE (B2, B4, B5, B7, B12, B17) |
| | WPAN RADIO | Bluetooth 4.0 LE |
| Optional Accessories | | Charging cradle, pistol grip, rubber boot, battery, AC adapter, cable, wrist lanyard, hand |
| | | strap. |

Newland China

