



NLS-MT65

PORTABLE DATA COLLECTOR

FEATURES

- Rugged Construction**

The NLS-MT65's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.2m drops to concrete.

- Superior Barcode Reading Performance**

When equipped with Newland's fifth-generation **UIMC**® technology, the new NLS-MT65 can decode even poorer quality barcodes, such as soiled or wrinkled labels, with ease.

- Heavily Customized Android**

The value-added features of the NLS-MT65, including application protection and admin tool, seek to shore up Android's data security.

- Diverse Functionalities**

The NLS-MT65 offers 1D/2D/BT/Wi-Fi/4G /3G /GPS/Camera/NFC functionalities to meet various application needs.



2D Barcode



1D Barcode



Android



4" Color Screen



GPS



IP65



4G



WiFi

NLS-MT65

Performance

| | |
|------------------|--|
| Processor | 1.5GHz quad-core processor |
| Operating System | Android 8.1 |
| Memory | 2GB RAM, 16GB ROM |
| Interface | Micro USB 2.0, Battery charging over USB supported |

Physical/Electrical

| | |
|-----------------------|---|
| Dimensions (L×W×H) | 166 × 73 × 26 mm |
| Weight | 330g (including battery) |
| Display | 4" WVGA (800×480) capacitive touch screen |
| Keypad | 30 keys (side keys included) with backlight |
| Notification | Vibration, speaker and multi-color LEDs |
| Battery | 3.7V, 3800mAh |
| Expected Battery Life | 10 hours |
| Expected Charge Time | 4.5-5 hours (charge via AC adapter) |
| Camera | 8 megapixels, auto focus, with LED flashlight |
| GPS | GPS (AGPS) |
| Expansion | Micro SD card (max. 128GB) slot |
| AC Adapter | Output: DC5V, 2.0A Input: AC100~240V, 50~60Hz |

Environmental

| | |
|-----------------------|---|
| Operating Temperature | -20°C to 50°C (-4°F to 122°F) |
| Storage Temperature | -30°C to 70°C (-22°F to 158°F) |
| Humidity | 5% to 95% (non-condensing) |
| Static Discharge | ±15 kV (air discharge), ±8 kV (direct discharge) |
| Drop | 1.2m drops to concrete (for six sides, one drop per side) |
| Sealing | IP65 |

Barcode Scanning

| | |
|--|--|
| 2D Scan Engine Laser aiming Mega-pixel | ID: Code128, Code 49, Code 16K, (GS1128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC-A, ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, Codabar, Code93, Code 11, Plessey, MSI Plessey, RSS. 2D: Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data Matrix, DotCode. |
|--|--|

Depth of Field

| | |
|---|---|
| Depends on barcode type and environment | Code39 (20mil) 90mm-580mm; EAN13 (13mil) 45mm-380mm Code39 (5mil) 75mm-180mm; DM (10mil) 50mm-180mm PDF417 (6.7mil) 70mm-170mm; QR (15mil) 40mm-220mm |
|---|---|

NFC

| | |
|---------------|---|
| 13.56MHz RFID | ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693 |
|---------------|---|

Wireless

| | |
|------------|--|
| WLAN RADIO | IEEE 802.11 a/b/g/n, 2.4GHz and 5GHz |
| WWAN RADIO | 2G 3G 4G |
| WPAN RADIO | Bluetooth 4.2 LE (Backward-compatible) |

Optional Accessories

Battery, AC adapter, cable etc.

Specifications are subject to change without notice.

2020/4/17

Version: V1.3

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@nlsan.com
Web: www.newlandaidc.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@nlsan.com
Web: www.newlandamerica.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com

Asia Pacific

Taiwan:
Add: 7F-6, No. 268, Liancheng Rd.,
Jhonghe Dist. 235, New Taipei City, Taiwan
Tel: +886 2 7731 5388
Email: info@newland-id.com.tw