INVOICE



Simple. Rugged. Reliable. 8i



- Prints full size, multi-part delivery receipts and invoices at point of delivery
- Rugged enough to be used in the front seat of delivery vehicle or carried into receiving area
- Powered by vehicle's 12-volt system (without voltage adapter), or used remotely with internal battery pack
- Contains up to 200 sheets of 8.5" x 11" or A4 paper



microFlash8i



microFlash **Impact Printer**



8 Mason Irvine, CA 92618, USA 949-458-0500 (tel) 949-458-0708 (fax) www.oneilprinters.com sales@oneilinc.com (e-mail)

Simple. Rugged. Reliable.

Rugged. The 8i case is made of unbreakable polyethylene plastic. We guarantee it in our warranty- no one else offers that.

Flash Memory. As your business needs change, so can your printer. We pioneered the use of Flash memory many years ago allowing you to change fonts and functions simply by connecting the printer to a computer. No need to return the printers for an upgrade.

We speak your language - any language. O'Neil has taken away the font and character limitations you find in other printers. In cooperation with Bit Stream™ Fonts, any international character set can be added to the 8i with a one-time minimal setup fee.

Plenty of Power. The 8i uses a standard DR36 nickel metal hydride battery with over 3,600 mAh of power. Enough power to print over 200 invoices on a single charge.

Flexible Power Options. The 8i runs off your 12 volt vehicle power without an expensive adapter.

No Paper lams. In the early 80's, O'Neil created a unique paper feed design that literally eliminates paper jams. It allows a lot of paper to fit in a small package. The printer can be held in any orientation – even upside down - without jamming. Perfect for portable applications.

Standard features include IRDA capability and an R\$232 serial port. Options include softcase carrying case a vehicle mounting bracket and a high capacity battery.

microFlash 8i (180) Portable Printer Specifications

Physical Ch	aracteristics:		
Size	15.5" x 11.75" x 4.25"	3.93.7 x 298.45 x 107.95mm	
Weight	101.4oz / 2875g		
Environment:		Communicatio	ns:

Media

Agency Approvals:

Operating Temp -20° C to 40° C Storage Temp -40° C to 70° C Charding Temp 5° C to 40° C Relative Humidity 10% to 90% noncondensing **ESD Protection** 8 kV Air, 4 kV Contact

Print Technology: 9 pin impact 180 Characters per inch

Print Head Print Speed Print Head Life 100 Million Dots Ribbon Cartridge 2.000.000 Characters

Memory Capacity Flash/RAM Memory: 4/1 Mbit Available Fonts 10 CPI Pica/Flite: 12 CPI Pica/Flite Int'l Characters Arab-T, Arab-S, Arab-E, Cyrillic (CY110 & CY210), Greek (GRDOS & GRWIN). Hebrew (HB110, HB210, HB310), Latin

Fonts & Languages

Power Source (input): 12-15V (AC Adapter) spike and surge protected DC lack 1 12-15V (Cigarette Adapter) spike and surge DC Jack 2 Optional Battery 12V Nickel Metal Hydride 3600 mAh

Battery Characteristics: 12V NiMH 3600mAH (DR 36) Endurance Approx, 224 invoices on one charge Battery Life 80% of original capacity after 400 cycles Recharding 3-4 Hours (printer connected to Cigarette or AC Adapters

Up to 38.4k baud. Cables available for most RS-232 Seria opular laptops and handhelds. IrDA IrDA compliant infrared data communications up to 115.2k baud.

Paper Fan-fold paper. 3" to 9.5" wide/A4 Number of Copies Original + 3 copies Capacity 200 Sheets

FCC B. CF. C-Tick Agency Warranty Warrantv 1 Year (including printer case)

Optional Accessory: Softcase with storage for AC, Cigarette adapters, Data cable, and Notebook./Hand held computers Mounting Brackets Locking/Non-Locking External Battery Charges

EUROPEAN OFFICE

Witan Court 285 Upper Fourth Street Witan Gate West Central Milton Keynes United Kingdom MK9 1FH +44 1908 393300 (tel) +44 1908 393400 (fax) www.oneilprinters.com sales@oneiluk.com (e-mail)