

This model is equipped with an alpha-numeric keypad and a graphical display. It is standard equipped with integrated barcode laser scanner, memory, a real-time clock and supplied with a rechargeable battery.

DATA COLLECTOR

OPL 9728

Barcode data collector with keypad and IrDA interface



Features

- Keypad with cellphone look and feel
- LCD display
- Small size and light weight
- Flash ROM and RAM memory
- IrDA interface

Benefits

- Less instructions required
- Clear overview
- Easy to carry
- Provides program and data storage
- Optical data transmission to cradle

Cabled

Wireless

Stationary

OEM

OPTICON
always scanning for new ID's

Specifications

OPL 9728 Barcode data collector with keypad and IrDA interface

Electrical specifications

Main battery pack: Li-Ion rechargeable 3,7 V / nom. 600 mAh

Main battery pack operating time: When making every 5 seconds 1 scan with Backlight OFF, 1 sec laserbeam on and 0.2 sec. green LED on and 0.2 sec. buzzer on, operating time is: approx. 45 hours

Main battery condition: Different operation conditions affect the operating time

Backup battery: Lithium rechargeable 3,5 mAh

Backup battery operating time: > 1 week backup

Battery management: When battery is low the data collector switches off automatically.

Charging method: The main battery in data collector will be charged through the cradle. The backup battery will be charged by the main battery.

Optical specifications

Light source: 650 nm visible laser diode

Scan method: vibrating mirror

Scan rate: 100 scans/sec

Decode rate: 100 decodes/sec

Reading angle: effective 44°

Reading pitch angle: +8 - +50° / -8 - -50°

Reading skew angle: ± 35°

Reading rotation angle: 20°

Reading width: 45 - 320 mm, depending on reading distance and bar code label resolution

Min. Resolution at PCS 0.9: 0.15 mm (6mil)

Min. PCS value: 0.45

Depth of field: 60 - 300 mm (UPC PCS0.9, resolution 1.00), 35 - 210 mm (UPC PCS0.9, resolution 0.5), 35 - 120 mm (UPC PCS0.9, resolution 0.25), 35 - 70 mm (UPC PCS0.9, resolution 0.15)

Identification

Supported barcode symbologies (1D): Chinese Post - Codabar incl. ABC and CX - Code 39 - Code 39 Full ASCII - Code 93 - Code 128 - EAN-8 incl. +2,+5 - EAN-13 incl. +2,+5 - EAN-128 - IATA - Industrial 2of5 - Interleaved 2of5 - Italian Pharmaceutical - ISBN - ISSN - Matrix 2of5 - MSI/Plessey - UK/Plessey - RSS-14 - RSS Limited - RSS Expanded - Telepen - UPC-A incl. +2,+5 - UPC-E incl. +2,+5

Optional symbologies: MicroPDF417 - PDF417 (if supported in application)

Functionality

Trigger mode: manual by trigger key

Memory FlashROM: 512 kB (O/S and program)

Memory RAM: 512 kB (data storage) / optional 1MB

Microprocessor: 16-bit

Real time clock: Quartz RTC, time and date programmable, leap year handling, (accuracy +/- 60 sec./month)

Display: 112x64 Pixels graphic LCD

Character fonts: min. 4 lines x 14 characters, max. 10 lines x 18 characters

Keyboard : 18 keys total

Keyboard function keys: 2 function keys

Keyboard mode: Alpha/Numeric mode

Programming: Functionality is provided by user application.

Communication specifications

Transmission speed IrDA: baudrate: 2400 - 115200 bps

Environmental specifications

Temperature in operation: -5 - +40 °C

Temperature in storage: -20 - +60 °C

Humidity in operation: 20 - 80 % (non condensing)

Humidity in storage: 20 - 90 % (non condensing)

Ambient fluorescent light immunity: 3.000 lux max

Ambient white light immunity: 3.000 lux max

Ambient direct sun light immunity: 50.000 lux max

Shock drop test: 1.5 m drop onto concrete surface

Shock vibration test: 12 - 100 Hz with 2G for 1 hour

Physical specifications

Dimensions: (l x w x d) 129 x 44 x 22.3 mm

Case material: ABS

Weight body: ca. 100 g

Regulatory

Laser safety class: IE C825, Class I laser product

EMC: EN 55022, EN 55024

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Mainhausen
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Lane Cove

Opticon Inc.
8, Olympic Drive
Orangeburg NY 10962 - 2511
U.S.A.
phone: toll free: 800-636-0090
local: 845-365-0090
fax: 845-365-1251
email: opticon@opticonUSA.com
internet: www.opticon.com

www.opticon.com

OPTICON
always scanning for new ID's