





#### ■ World Leading Active Matrix TFT-LCD Panel

Truly flat LCD screen delivers razor sharp images

## ■ Hi Performance Image Processing Circuit

3D comb filter and deinterlace function realize perfect images

## ■ Real Industrial Mechanical Design

Rigid case comes with Heavy duty metal vessel, LCD protection glass

#### ■ Versatile terminals for Security and Industrial Solution

Multiple input and output of Video(BNC Type), Audio, S-Video and RGB

Video	
Screen Size	20"
Resolution	1600 x 1200@60Hz
Contrast Ratio	400:1
Brightness	250cd/m2
Aspect Ratio	4:3
Color Depth	16.7M
Viewing Angle(H/V)	176°/176°
Pixel Pitch	0.255mm
Response Time	16ms
Scanning Frequency(Horizontal)	31 ~ 79.9KHz
(Vertical)	56 ~ 75Hz
Video System	NTSC

Audio			
	Built-in Speakers	Yes	
	Gradual Volume Increase	Yes	

Terminals		
RGB In (15-pin)	1	
Video In(BNC Jack)	2	
Video Out(BNC Jack)	2	
Audio In	2	
Audio Out	2	
S-Video In	1	
S-Video Out	1	
Component In	1	
DVI In	1	
PC stereo In	1	

Remote Control			
	Transmitter	Yes	

<sup>\*</sup> Specification and Design are subject to change without prior notice.

eci			

Special Features	
2D comb Filter	Yes
Deinterlace Function	Yes
USB Hub	Not Available
DC 12V Power Outlet	Not Available
LCD Protection Glass	Yes
Rack Mountable Kit	Optional
Camera Mounting Hole	Yes
Multi-lingual Menus	English, Spanish, French,
	German, Italian
VESA <sup>™</sup> Standard Compatible	Yes

# **Additional Information**

Cabinet Dimensions	
WxHxD	19.3"x16.5"x2.5"/490x420x65
Weight	18.8lbs/8.5kg
Dimensions with Packaging	
WxHxD	21"x18.3"x7.9"/535x465x200
Weight	23.3lbs/10.5kg
Power Consumption	60W
Power Source	AC110~230V(50/60Hz)

	Tilt Stand	Yes	
Warranty			
	Warranty: Parts/Labor	1 Year/1 Year	

MTBF (Approx.)

Finish

Black

30K hrs.

## **Regulations**

TUV-NRTL(same as UL), CB, FCC(B), CE-EMC(LVD)