

# POS X

POINT OF SALE  
PERFECTED

## Xr200 SERIES

IMPACT RECEIPT PRINTER

The Xr200 Impact Receipt Printer is built to last. Its thick casing dampens sound, making the Xr200 the quietest impact printer in its class. Two-Color printing, RJ11 Cash Drawer port, OPOS drivers and up to 3-Ply printing are among this printer's many features. Boasting a splash-resistant housing and wall mount capabilities, it is the perfect choice for Kitchen areas and other hot and humid environments.



### KEY FEATURES

- Splash-resistant housing is ideal for kitchens
- Choose from tearbar or auto-cutter models
- ESC/POS and OPOS compatible
- Wall mountable
- 3 year warranty

receipt printer

# Xr200 Series Specifications

PART NUMBER	XR200ABP	XR200ABS	XR200BBP	XR200BBS
<b>SPECIFICATIONS</b>				
Interfaces	Parallel IEEE-1284	Serial RS-232C	Parallel IEEE-1284	Serial RS-232C
Emulation	Epson TM-U200, Epson TM-U300, Citizen iDP-3540, Star SP200, Verofone P900			
Print Method	9-pin Serial Dot Matrix			
Printing Speed	4 lines/sec			
Number of Total Dots	400Dots/line			
Resolution	160 DPI			
Printing Direction	Bi-directional with logical seeking			
Effective Printing Width	2.5"			
<b>CASH DRAWER PORTS</b>	2 Circuits (24V, 1A max)			
<b>RELIABILITY</b>				
MCBF	5,000,000 Lines			
Printhead	150 Million Characters			
<b>PAPER</b>				
Type	Roll Paper			
Width	3" (76.2mm)			
Roll Diameter	3" (76.2mm)			
Copies	Original + 2 Copies			
<b>NUMBER OF COLUMNS</b>	Epson TM-U200 Emulation 42/35, 40/33		Star SP200 Emulation 42/35 Other Emulation 40/33	
<b>INK RIBBON</b>	EPSON ERC-23, ERC-38 Black, Purple, Black/Red			
<b>AUTO CUTTER</b>				
Type	Guillotine		Tear Bar	
Life	1,000,000 Cuts		n/a	
Paper Thickness	0.002" (0.065mm) - 0.005(0.13mm)			
Cutting Method	Full/Partial Cut		n/a	
<b>PHYSICAL</b>				
Dimension	6.88"(w) x 8.60"(d) x 5.20"(H)			
Weight	4.21 lbs		3.64 lbs	
Color	Black			
<b>ELECTRICAL</b>	(input) 100 - 240 Vac 50/50 Hz		(output) 24Vdc/2.5A	
<b>ENVIROMENTAL</b>				
Temperature	41° F to 104° F operating -4° F to 140° F storage			
Humidity	35%-80% non condensing (operation)		10%-90% non condensing (storage)	
<b>WARRANTY</b>	3 Year		1 year on autocutter assembly and print head	
<b>CERTIFICATIONS</b>	FCC, MIC, UL, CE, CCC, RoHs(TUV)			
<b>OPERATING SYSTEM</b>	WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/OPOS driver available			

