

Magellan® 2300HS Ω

Horizontal Scanner



Mechanical

Dimensions

Height: 6.0" / 15.2 cm
Width: 6.0" / 15.2 cm
Depth: 3.41" / 8.66 cm

Weight: 2.5 lb / 1.1 kg

Environmental

Temperature rating

Operating: 50° to 104° F / 10° to 40° C
Storage/transport: -40° to 158° F / -40° to 70° C

Humidity

Operating: 5 to 95% NC
Storage/transport: 5 to 95% NC

Optical

Scan lines: 20

Motor Speed: 6,000 RPM

Depth-of-field: 8.0" / 23.3 cm

Read height: 6.0" / 15.2 cm

Decoding Capability

The Magellan® 2200VS autodiscriminates between all of the following supported symbologies:

- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- Reduced Space Symbology (RSS-14, expanded & stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

Features:

- Omega Tek™ Productivity Technology
- Aggressive horizontal scan volume
- FirstStrike® advanced decoding software
- RSS Decoding capability
- Flash memory for easy software upgrades
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Host diagnostic reporting
- Optional EAS functionality
- Optional Productivity Index Reporting™ Software
- 2005 Sunrise compliant



"Nothing Beats a Magellan®"

Data Sheet

Electrical

AC Power requirements

90-265 VAC, 47-63 Hz
4.0 Watts (nominal)
9.6 Watts (maximum)
2.5 Watts (sleep mode)

Communications

Host: Standard RS-232, IBM 46XX, IBM USB, USB Keyboard
Other: Powered RS-232 auxiliary port

Safety and Regulatory

Electrical: EN60 950 (TUV Europe)PSE-Mark (Japan); UL 60950 (USA)CSA 60950 (Canada)

Emissions: CISPR22-B (World) , FCC part 15 Class B (USA), VCCI-B (Japan), EN 55022-B (Europe), NOM (Mexico)

Laser Safety: CDRH Class IIa (USA/Canada), EN 60825-1 Class 1 (Europe), IEC 60825-1 Class 1 (World)

(CAUTION: Laser Radiation – do not stare into beam); IEC 60825 Class 1 (Europe)



Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI and VII models available from Checkpoint® Systems.

Good read acknowledgement with Sensormatic OPOS and JPOS compatible.

PSC Inc.
959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140



© 2005 PSC, Inc. All rights reserved. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • PSC, the PSC logo, Magellan, and First Strike are registered trademarks of PSC Inc. • Productivity Index Reporting (PIR) is a trademark of PSC Inc. All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site www.psc.com. • Product specifications are subject to change without notice.

R40-0042-US C 0605

