

# MT-6620 MOBILE TERMINAL



The MT-6620 rugged handheld terminal is developed for a wide range of applications in the mobile field services. It utilizes the Intel technology to provide a desktop Windows 10 experience on a 6-inch mobile device. With its WiFi and 3G Network capability your operation is always connected. Furthermore the MT-6620 supports functions such as 1D/2D barcode scanning, NFC, infrared communication, GPS, photographing and voice communication. It can be used in various fields such as retail, manufacturing, fast moving consumer goods, logistics, warehousing, governments and public utilities. It is also best suitable for outdoor use with its high brightness screen, dust and water resistance.

#### SPECIAL FEATURES

Rugged Handheld with IP65 Windows 10 IOT, 32-bit High brightness sunshine readable screen Gorilla Glass Capacitive multi-touch that supports glovetouch 5000mAh Removable Battery

### OPTIONAL

1D barcode reader 2D barcode reader NFC Docking Station Pistol Grip

### TECHNICAL DATA

# MT-6620



ITEM	MT-6620		
CPU	Intel® Atom™ x5-Z8350 CPU @1.44 GHz		
LCD	Industrial-grade 5.98" IPS display with 1280x720 resolution		
Touch	Capacitive Multi Touch (supporting operation with gloves)		
RAM / ROM	2GB LPDDR3 RAM / 32GB ROM		
I/O Interface	1 x Micro USB OTG		
	1 x Micro SD up to 128GB, supports SDHC/SDXC		
	1 x Micro SIM		
	1 x 3.5mm Headphone Jack		
	1 x Microphone		
Operating System	Windows 10 IOT, 32-bit		
Wireless Communication	WiFi 802.11 (a/b/g/n) Frequency 2.4GHz + 5 GHz Dual Band BT4.0 (BLE) class 1.5		
WWAN (option)	3G		
	WCDMA(900/2100MHz), GSM 900/1800MHz, HSDPA 7.2Mbps, HSUPA 5.76 Mbps)		
Button / Keyboard	Power Button, Windows Button, Minus Volume, Plus Volume, Barcode Trigger		
Sensor	Compass, Gravity Acceleration Sensor, Gyroscope, Start & Shut Down Indicator Light		
IrDA	Supports launch and receive infrared ray		
Audio	Built-in microphone		
	Built-in 8Ω / 0.8W speaker		
	1 x 3.5mm Headphone Jack Front: 2MP		
Camera	Rear: 5MP		
Battery	3.7V, 5000mAh (Removable Battery Design)		
Working Time	4 hours (default 50% volume, default 200 lumens brightnessplay 720 HD video)		
Power Supply	Input: DC100~240V, 50/60Hz Output: DC 5V, 2.5A, Micro USB Interface		
NFC	13.56MHz NFC		
GPS	Supporting GPS / QZSS / Glonass		
Barcode Reader (optional)	1D: Honeywell N4313/Optical resolution: 5mil, scan speed: 50 times/s, supported codes: UPC/EAN, Bookland EAN, UCC Coupon Code, ISSN EAN, Code 128, GS1-128, ISBT 128, Code 39, Trioptic Code 39, Code 32, Code 93, Code 11		
	2D: Honeywell N3680 hard decode; Optical resolution: 5mil, scan speed: 50 times/s, supported codes: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverse, Han Xin, Han Xin Inverse		

\*Specification is subject to change without prior notice



PARTNER TECH USA INC. 15320 Barranca Parkway Suite 150. Irvine, CA 92618 Phone: +1-949-598-1888 sales@partnertechcorp.com

### TECHNICAL DATA

## MT-6620



ITEM	MT-6620			
IP-Class	IP65			
Drop Resistance	1,2m on wood floors			
ESD	8kV air discharge, 4kV contact discharge			
Dimensions	93mm (W) x 20.7mm (D) x 185mm (H)			
Weight	380g			
Environment		Operating:	Storage:	
	Temperature:	-10°C ~ +50°C	-30°C ~ +70°C	
Packing	Micro USB Power adapter, battery, hand strap			
Options	1D or 2D barcode reader, NFC, Docking Station, Pistol Grip			
	4 GB RAM, 64 GB ROM (*only with Minimum Order of Quantity)			

\*Specification is subject to change without prior notice





#### PARTNER TECH USA INC. 15320 Barranca Parkway Suite 150. Irvine, CA 92618 Phone: +1-949-598-1888 sales@partnertechcorp.com