

# PARTNER

CARE . TRUST . RESPONSIBILITY

## PM-116 POS Monitor

### The multifunctional Display



The PM-116 is the new compact and modern POS Monitor. It is small and has a light weight design.

The monitor has a modern and stylish design. Through various applications it fits in many different business environments such as retail, hospitality, speciality shops etc.

The monitor can be used as Digital Signage, Customer Display, Touch-screen or as Operator Display as well as in many other business areas.

Through the pole stand the monitor is adjustable and can be fixed easily in the required position by the individual operator.

#### **Special Features:**

- Compact & small
- Light weight design
- Stylish & multifunctional
- Wide screen, support 1024x768
- Front bezel dust & spill resistant
- OSD controlled by software
- LED backlight LCD, energy saving

#### **Optional:**

- 5-wire resistive touch panel (USB or RS232 interface)
- Wallmount bracket
- Adjustable pole

## POS Monitor PM-116

### Technical data

Item	PM-116									
LCD Display	11.6" TFT-LCD panel (w/o touch)									
Pixel Pitch	0.1875(H) x 0.1875(V) mm									
Max. Resolution	1360/1366 x 768									
Active Area	256.13 x 144.00 mm									
Contrast Ratio	400 (Typ)									
Brightness	200 cd/m <sup>2</sup>									
Display Color	262,144 colors									
Viewing Angle	L/R 45° ~ 45° U/D 15°~35°									
OSD (On Screen Display)	Software Control: Brightness, Contrast, Display Position, RGB Adjustment, Position Auto Adjustment, Color Auto Adjustment									
Power Supply	AC 100V ~ 240V/ DC12V/4.16A 50 watt									
Environment	<table border="1"><thead><tr><th></th><th>Operating</th><th>Storage</th></tr></thead><tbody><tr><td>Temperature</td><td>0~40 °C</td><td>-20~80 °C</td></tr><tr><td>Humidity</td><td>15% ~ 80%</td><td>15% ~ 80%</td></tr></tbody></table>		Operating	Storage	Temperature	0~40 °C	-20~80 °C	Humidity	15% ~ 80%	15% ~ 80%
	Operating	Storage								
Temperature	0~40 °C	-20~80 °C								
Humidity	15% ~ 80%	15% ~ 80%								
Certification	CE, FCC, BSMI, LVD									
Accessory	Adaptor, VGA cable									
Options	5-wire resistive touch panel (USB or RS232 interface), wallmount bracket, adjustable pole									



Dual Display Monitor Stand



Individual angle adjust  
(pole type)



Variable height adjust  
(pole type)