

Care.

Trust.

Responsibility.



PT-6212

All-In-One POS Terminal

Features At-A-Glance

Integrated Thermal Receipt Printer

Integrated 3-Track MSR

Integrated Customer Display

All-In-Once Convenience



Specifications

Item	PT-6212	
Processor	Intel Celeron-M Processor @ 1 GHz	
System Memory	1 G (up to 2G)	
Display	12.1" TFT LCD	
Resolution	800 x 600 or 1024 x 768	
Touch Screen	5 wire resistive touch	
LCD Brightness	250 Nit	
Network	10/100/1000 Mbps onboard ethernet controller	
Storage	SATA 3.5" 80GB hard drive	
I/O Interface	· 4 * COM ports · 1 * RJ11 port (+24V) · 1 * PS2 Keyboard port · 1 * RJ-45 LAN port · 4 * USB ports · 1 * DC +12V	· 4 * COM ports · 1 * RJ11 port (+24V) · 1 * PS2 Keyboard port · 1 * RJ-45 LAN port · 4 * USB ports · 1 * DC +12V · 1 * VGA port
Operation System	WEPOS / POSReady / Windows 2000 / CE.Net / Linux	
Power Supply	AC 100V-240V / DC12V / 12.5A 150 watt power adaptor	
Operating Temperature	32° F ~ 104° F	
Storage Temperature	68° F ~ 140° F	
Operating Humidity	15% ~ 80%	
Storage Humidity	15% ~ 80%	
Dimensions	12.9" (W) x 11.3" (D) x 9.7" (H)	
Integrated Peripherals	· 3 track magnetic card reader (MSR) · 2" x 20" Customer display module · 3" thermal receipt printer with cutter and control board	
Color	Dark charcoal	
Options	4G uSSD, RFID reader, WLAN	

Features In Detail



Integrated printer



Integrated MSR



12.1" Touch Screen



Integrated customer display



Modular design for easy maintenance



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.