

Care.

Trust.

Responsibility.



RP-320

Thermal Receipt Printer

Features At-A-Glance

200 mm/sec High Speed Printing

Wall Mountable

Supports Full & Partial Cut

Optional Water-Resistant Cover



Specifications

		RP-320
Printing	Method	Direct Thermal
	Speed	7.87"/sec
	Width	2.83" (512 Dots/Line)
	Resolution	180 DPI
Paper	Type	Thermal Printer
	Width	1.96" ~ 3.24"
	Thickness	0.002" ~ 0.003"
	Roll Diameter	3.14"
	Roll Core Inner	0.49" ~ 0.01"
Reliability	Tph Life	160 km
	Mcbf	60,000,000 Lines
Auto Cutter		1,500,000 Cuts (Guillotine)
Sensor	Standard	Paper End, Cover Open
	Option	Paper Low, Black Mark Sensor
Interface	Standard	USB
	Option	Serial, Parallel, Ethernet
Emulation		ESC/POS Command Compatible
Driver		Windows Printer Driver (7, XP, 200, 2003 VISTA), WEPOS, OPOS, Linux, JavaPOS
Power	Type	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24V DC / 2.5A
Temperature	Operation	41° F ~ 104° F
	Storage	-4° F ~ 140° F
Dimensions		5.98" (W) x 7.79" (D) x 5.94" (H)
Weight		3.7 Lbs
Color		Black, Cool White

Features In Detail



Cover Paper Opening



Supports Paper Width
1.96" to 3.24"



Interface



Water Resistant Cover



Wall Mountable



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.