



CARE . TRUST . RESPONSIBILITY

SP-630 TOUCH POS SYSTEM

GREAT VALUE



The SP-630 is a smart POS system designed to meet the needs of today's power hungry POS and customer service applications. The fanless Celeron N2807 processor, and up to 4GB of RAM, are combined in an elegant touch screen unit that features some of the most advanced and cost effective features found on any POS system.

SPECIAL FEATURES

- Intel® Celeron® N2807 processor
- DDR3L memory up to 4GB
- Flexible modular design
- Convenient wall mount and wide tilt angle
- Dust-and spray-resistant front panel (IP65 rating)

OPTIONAL

- Supports optional customer-facing display (2x 20 VFD, 7", 11.6" or 15")
- Optional peripherals: 3-track encryption-capable MSR, Bio reader, Chip Card reader, RFID/NFC

SP-630

Item	SP-630									
CPU	Intel® Celeron processor N2807 (1M Cache, 1.58 GHz up to 2.16 GHz)									
LCD	15" Active TFT color LCD, resolution 1024 x 768									
Touch	5-wire Resistive touch									
Memory	204pin DDR3L SO-DIMM 2GB (Support up to 4GB)									
Ethernet	IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet									
Storage	Internal 2.5" type SATA HDD x 1									
I/O Interface	3 * COM ports (COM1~3 at back I/O, powered with DC +5/+12V) 1 * DB-15 VGA port 1 * RJ11 port for 2 cash drawer(+24V) 1 * RJ-45 LAN port with activity and link LEDs 3 * USB 2.0, 1*USB 3.0 1 * DC +12V power adaptor connector 1 * DC +12V output									
Expansion Options	1 * Mini PCI-e, Support Wireless Lan Module									
Optional Peripherals	3 tracks magnetic reader Customer display module (2 x 20 VFD) Biometric Reader, Smart Card Reader, I-Button, RFID reader 2nd 11.6" monitor(Dual screen)									
Operation System	Windows 7, POSReady 7, Windows 8.1, Windows 8.1 Industry pro, Windows 10, Linux (ubuntu)									
Power Supply	AC100~240V/DC12V, 7.5A, 90 watt power adaptor									
Dimensions	Physical: 14.17in (W) x 9.92in (D) x 13.82in (H)									
Environment	<table border="0"> <tr> <td></td> <td>Operating:</td> <td>Storage:</td> </tr> <tr> <td>Temperature:</td> <td>32°F~ 104°F</td> <td>-4°F~ 140°F</td> </tr> <tr> <td>Humidity:</td> <td>15%~80%</td> <td>15%~80%</td> </tr> </table>		Operating:	Storage:	Temperature:	32°F~ 104°F	-4°F~ 140°F	Humidity:	15%~80%	15%~80%
	Operating:	Storage:								
Temperature:	32°F~ 104°F	-4°F~ 140°F								
Humidity:	15%~80%	15%~80%								
Certification	CE, FCC, VCCI, BSMI, CCC, CB									

*Specification is subject to change without prior notice



PARTNER TECH USA INC.
 15320 Barranca Parkway Suite 150.
 Irvine, CA 92618
 TEL: +1-949-598-1888
 sales@partnertechcorp.com

