

# PARTNER

CARE . TRUST . RESPONSIBILITY

## SP-650 TOUCH POS SYSTEM

GREAT VALUE



The SP-650 series from Partner Tech is a high performance smart POS system designed to meet the needs of today' power hungry POS and customer service applications. The fanless Celeron J1900 processor, and up to 8GB of RAM, are combined in an elegant touch screen unit that features some of the most advanced and cost effective features found on any POS system.

### SPECIAL FEATURES

- Intel® Celeron® J1900 Processor
- DDR3L memory supports up to 8GB (max)
- Flexible modular design and dual display supports digital signage
- Convenient wall mount and wide tilt angle
- Splash and dust resistant front bezel, IP66

### OPTIONAL

- Supports optional customer-facing display (2x 20 VFD, 7", 11.6" or 15")
- Optional peripherals: 3-track encryption-capable MSR, Bio reader, Chip Card reader, RFID/NFC

**SP-650**

Item	SP-650
CPU Type	Intel® Celeron processor J1900 (2M Cache, 2.0 GHz up to 2.42 GHz)
LCD	15" Active TFT color LCD, resolution 1024 x 768, brightness 350 nits
Touch	Projected Capacitive Touch
Memory	204pin DDR3L SO-DIMM 8GB
Ethernet	IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet
Storage	Internal 2.5" type SATA HDD x 1
I/O Interface	3 * COM ports (COM1-3 at back I/O, powered with DC +5/+12V) 1 * DB-15 VGA port 1 * DB-25 for LPT port (option) 1 * RJ11 port for 2 cash drawer(+24V) 1 * RJ-45 LAN port with activity and link LEDs 2 * Audio ports (1 * Line-out , 1 * MIC-in), (option) 3 * USB 2.0, 1 * USB 3.0 1 * DC +12V power adaptor connector
Expansion Options	1 * Mini PCI-e, Support Wireless Lan Module
Optional Peripherals	3 tracks magnetic reader Customer display module (2 x 20 VFD) Biometric Reader, Smart Card Reader, I-Button, RFID reader 2nd 11.6" monitor(Dual screen)
Operation System	Windows 7, POSReady 7, Windows 8.1, Windows 8.1 Industry pro, Windows 10, Linux (ubuntu)
Power Supply	AC100~240V/DC12V, 7.5A, 90 watt power adaptor
Dimensions	Physical : 14.17in(W) x 9.45in(D) x 14.37in(H), (LCD 15 tilt angle)
Operating Temp	32°F~ 104°F
Storage Temperature	-4°F~ 140°F
Humidity	15%~80%
Certification	CE, FCC Class B, VCCI, BSMI, CCC

\*Specification is subject to change without prior notice



**PARTNER TECH USA INC.**  
15320 Barranca Parkway Suite 150.  
Irvine, CA 92618  
TEL: +1-949-598-1888  
sales@partnertechcorp.com

