

# PLANAR PS4200

The Planar PS4200 is a 42" professional LCD display delivering multiple connectivity options, enhanced durability, and superior visual performance. To meet the requirements of demanding public signage and corporate applications, the Planar PS4200 provides full HD 1080p resolution with advanced features such as automatic/manual backlight control, video wall support, and RS-232 control. For added protection, the metal bezel on the Planar PS4200 improves durability and reduces heat load on the LCD. The Planar PS4200 is the ideal combination of value, performance, and reliability for any professional large format monitor application.



# **FEATURES**

Comprehensive set of data and video inputs

Durable metal bezel

Wide range of advanced features for professional applications

Superior full HD 1080p image quality with 500 cd/m<sup>2</sup> brightness

Display resolution Aspect ratio 16:9 Display type LCD Active Matrix Flat Panel Display (TFT) Viewable size 42" diagonal Cabinet dimensions (WxHxD) 39.1" x 23.0" x 4.7" (992.0mm x 585.0mm x 119.6mm) Bezel width 1.1" (29mm) Brightness (typical) 500 cd/m² Response time (typical) 5 ms Frame rate 60Hz Contrast ratio (typical) 1500:1 Full viewing angle 178° Color gamut 7296 NTSC Display weight 54 lbs (25 kg) Shipping weight 62 lbs (28 kg) Backlight type CCFL (cold cathode fluorescent lamp) Line voltage 100 - 240V; 50/60Hz Power consumption (max) 190W (Max) Ambient noise Operating temperature range Operating temperature range Operating humidity range Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control Auto brightness control Ambient light sensor Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes		PLANAR PS4200
Aspect ratio Display type LCD Active Matrix Flat Panel Display (TFT) Viewable size 42" diagonal 39.1" x 23.0" x 4.7" (992.0mm x 585.0mm x 119.6mm) Bezel width 1.1" (29mm) Brightness (typical) 500 cd/m² Response time (typical) 5 ms Frame rate 60Hz Contrast ratio (typical) 1500:1 Full viewing angle 178° Color gamut 72% NTSC Display weight 54 lbs (25 kg) Shipping weight 62 lbs (28 kg) Backlight type CCFL (cold cathode fluorescent lamp) Line voltage 100 - 240V; 50/60Hz Power consumption (max) 190W (Max) Ambient noise Panelss Operating temperature range Operating temperature range Operating temperature range Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio output RCA jack, external speaker connector (10W x 2) Display control RS-323C in/out, IR Remote Control, Keypad Auto brightness control Enclosure Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes		
Display type  LCD Active Matrix Flat Panel Display (TFT)  Viewable size  42" diagonal  39.1" x 23.0" x 4.7" (992.0mm x 585.0mm x 119.6mm)  Bezel width  1.1" (29mm)  Brightness (typical)  500 cd/m²  Response time (typical)  5 ms  Frame rate  60Hz  Contrast ratio (typical)  1500:1  Full viewing angle  178°  Color gamut  72% NTSC  Display weight  54 lbs (25 kg)  Shipping weight  52 lbs (28 kg)  Backlight type  CCFL (cold cathode fluorescent lamp)  Line voltage  100 - 240V; 50/60Hz  Power consumption (max)  Ambient noise  Operating temperature range  Operating temperature range  Operating temperature range  Safety regulations  FCC Class A, UL, CE  Inputs  HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio output  Phone jack and L/R RCA jack  Audio output  RCA jack, external speaker connector (10W x 2)  Display control  Ambient light sensor  Enclosure  Metal, industrial  Display orientation  Landscape  Speakers  12W x 2 built-in  Mounting  VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Display resolution	FHD 1080p (1920x1080)
Viewable size42" diagonalCabinet dimensions (WxHxD)39.1" x 23.0" x 4.7" (992.0mm x 585.0mm x 119.6mm)Bezel width1.1" (29mm)Brightness (typical)500 cd/m²Response time (typical)5 msFrame rate60HzContrast ratio (typical)1500:1Full viewing angle178°Color gamut72% NTSCDisplay weight54 lbs (25 kg)Shipping weight62 lbs (28 kg)Backlight typeCCFL (cold cathode fluorescent lamp)Line voltage100 - 240V; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Aspect ratio	16:9
Cabinet dimensions (WxHxD)39.1" x 23.0" x 4.7" (992.0mm x 585.0mm x 119.6mm)Bezel width1.1" (29mm)Brightness (typical)500 cd/m²Response time (typical)5 msFrame rate60HzContrast ratio (typical)1500:1Full viewing angle178°Color gamut72% NTSCDisplay weight54 lbs (25 kg)Shipping weight62 lbs (28 kg)Backlight typeCCFL (cold cathode fluorescent lamp)Line voltage100 - 240V; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Display type	LCD Active Matrix Flat Panel Display (TFT)
Bezel width 1.1" (29mm) Brightness (typical) 500 cd/m² Response time (typical) 5 ms Frame rate 60Hz Contrast ratio (typical) 1500:1 Full viewing angle 178° Color gamut 72% NTSC Display weight 54 lbs (25 kg) Shipping weight 62 lbs (28 kg) Backlight type CCFL (cold cathode fluorescent lamp) Line voltage 100 - 240V; 50/60Hz Power consumption (max) 190W (Max) Ambient noise Fanless Operating temperature range 0-40°C (32 -104°F) Operating humidity range 10-90% RH non-condensing Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Ambient light sensor Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Viewable size	42" diagonal
Brightness (typical)500 cd/m²Response time (typical)5 msFrame rate60HzContrast ratio (typical)1500:1Full viewing angle178°Color gamut72% NTSCDisplay weight54 lbs (25 kg)Shipping weight62 lbs (28 kg)Backlight typeCCFL (cold cathode fluorescent lamp)Line voltage100 - 240v; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA JackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Cabinet dimensions (WxHxD)	
Response time (typical) 5 ms  Frame rate 60Hz  Contrast ratio (typical) 1500:1  Full viewing angle 178°  Color gamut 72% NTSC  Display weight 54 lbs (25 kg)  Shipping weight 62 lbs (28 kg)  Backlight type CCFL (cold cathode fluorescent lamp)  Line voltage 100 - 240V; 50/60Hz  Power consumption (max) 190W (Max)  Ambient noise Fanless  Operating temperature range 0-40°C (32 -104°F)  Operating humidity range 10-90% RH non-condensing  Safety regulations FCC Class A, UL, CE  Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input Phone jack and L/R RCA jack  Audio output RCA jack, external speaker connector (10W x 2)  Display control RS-232C in/out, IR Remote Control, Keypad  Auto brightness control Ambient light sensor  Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Bezel width	1.1"(29mm)
Frame rate 60Hz  Contrast ratio (typical) 1500:1  Full viewing angle 178°  Color gamut 72% NTSC  Display weight 54 lbs (25 kg)  Shipping weight 62 lbs (28 kg)  Backlight type CCFL (cold cathode fluorescent lamp)  Line voltage 100 - 240V; 50/60Hz  Power consumption (max) 190W (Max)  Ambient noise Fanless  Operating temperature range 0-40°C (32 -104°F)  Operating humidity range 10-90% RH non-condensing  Safety regulations FCC Class A, UL, CE  Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input Phone jack and L/R RCA jack  Audio output RCA jack, external speaker connector (10W x 2)  Display control RS-232C in/out, IR Remote Control, Keypad  Auto brightness control Ambient light sensor  Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Brightness (typical)	500 cd/m <sup>2</sup>
Contrast ratio (typical)  Full viewing angle  Color gamut  72% NTSC  Display weight  54 lbs (25 kg)  Shipping weight  62 lbs (28 kg)  Backlight type  CCFL (cold cathode fluorescent lamp)  Line voltage  100 - 240V; 50/60Hz  Power consumption (max)  Ambient noise  Operating temperature range  Operating humidity range  Safety regulations  FCC Class A, UL, CE  Inputs  HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input  Audio output  RCA jack, external speaker connector (10W x 2)  Display control  Auto brightness control  Ambient light sensor  Enclosure  Metal, industrial  Display orientation  Speakers  12W x 2 built-in  Mounting  VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Response time (typical)	5 ms
Full viewing angle178°Color gamut72% NTSCDisplay weight54 lbs (25 kg)Shipping weight62 lbs (28 kg)Backlight typeCCFL (cold cathode fluorescent lamp)Line voltage100 - 240V; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Frame rate	60Hz
Color gamut 72% NTSC  Display weight 54 lbs (25 kg)  Shipping weight 62 lbs (28 kg)  Backlight type CCFL (cold cathode fluorescent lamp)  Line voltage 100 - 240V; 50/60Hz  Power consumption (max) 190W (Max)  Ambient noise Fanless Operating temperature range 0-40°C (32 -104°F) Operating humidity range 10-90% RH non-condensing  Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input Phone jack and L/R RCA jack  Audio output RCA jack, external speaker connector (10W x 2)  Display control RS-232C in/out, IR Remote Control, Keypad  Auto brightness control Ambient light sensor  Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Contrast ratio (typical)	1500:1
Display weight 54 lbs (25 kg)  Shipping weight 62 lbs (28 kg)  Backlight type CCFL (cold cathode fluorescent lamp)  Line voltage 100 - 240V; 50/60Hz  Power consumption (max) 190W (Max)  Ambient noise Fanless Operating temperature range 0-40°C (32 -104°F) Operating humidity range 10-90% RH non-condensing  Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input Phone jack and L/R RCA jack  Audio output RCA jack, external speaker connector (10W x 2)  Display control RS-232C in/out, IR Remote Control, Keypad  Auto brightness control Ambient light sensor  Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Full viewing angle	178°
Shipping weight Backlight type CCFL (cold cathode fluorescent lamp) Line voltage 100 - 240V; 50/60Hz Power consumption (max) Ambient noise Fanless Operating temperature range O-40°C (32 -104°F) Operating humidity range Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Ambient light sensor Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Color gamut	72% NTSC
Backlight typeCCFL (cold cathode fluorescent lamp)Line voltage100 - 240V; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Display weight	54 lbs (25 kg)
Line voltage100 - 240V; 50/60HzPower consumption (max)190W (Max)Ambient noiseFanlessOperating temperature range0-40°C (32 - 104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Shipping weight	62 lbs (28 kg)
Power consumption (max)  Ambient noise Fanless Operating temperature range O-40°C (32 -104°F) Operating humidity range Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Backlight type	CCFL (cold cathode fluorescent lamp)
Ambient noise Operating temperature range O-40°C (32 -104°F) Operating humidity range Safety regulations FCC Class A, UL, CE Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Ambient light sensor Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Line voltage	100 - 240V; 50/60Hz
Operating temperature range0-40°C (32 -104°F)Operating humidity range10-90% RH non-condensingSafety regulationsFCC Class A, UL, CEInputsHDMI, DVI, VGA, Composite Video, Component Video, S-VideoAudio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Power consumption (max)	190W (Max)
Operating humidity range  Safety regulations  FCC Class A, UL, CE Inputs  HDMI, DVI, VGA, Composite Video, Component Video, S-Video  Audio input  Phone jack and L/R RCA jack  Audio output  RCA jack, external speaker connector (10W x 2)  Display control  RS-232C in/out, IR Remote Control, Keypad  Auto brightness control  Ambient light sensor  Enclosure  Metal, industrial  Display orientation  Landscape  Speakers  12W x 2 built-in  Mounting  VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Ambient noise	Fanless
Safety regulations Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Ambient light sensor Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Operating temperature range	0-40°C (32 -104°F)
Inputs HDMI, DVI, VGA, Composite Video, Component Video, S-Video Audio input Phone jack and L/R RCA jack Audio output RCA jack, external speaker connector (10W x 2) Display control RS-232C in/out, IR Remote Control, Keypad Auto brightness control Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Operating humidity range	10-90% RH non-condensing
Audio inputPhone jack and L/R RCA jackAudio outputRCA jack, external speaker connector (10W x 2)Display controlRS-232C in/out, IR Remote Control, KeypadAuto brightness controlAmbient light sensorEnclosureMetal, industrialDisplay orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Safety regulations	FCC Class A, UL, CE
Audio output RCA jack, external speaker connector (10W x 2)  Display control RS-232C in/out, IR Remote Control, Keypad  Auto brightness control Ambient light sensor  Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Inputs	HDMI, DVI, VGA, Composite Video, Component Video, S-Video
Display control  Auto brightness control  Enclosure  Display orientation  Speakers  Mounting  PC Mounting: 100x200mm; 6 holes	Audio input	Phone jack and L/R RCA jack
Auto brightness control Enclosure Metal, industrial Display orientation Landscape Speakers 12W x 2 built-in Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Audio output	RCA jack, external speaker connector (10W x 2)
Enclosure Metal, industrial  Display orientation Landscape  Speakers 12W x 2 built-in  Mounting VESA: 400 x 200mm; 8 holes  PC Mounting: 100x200mm; 6 holes	Display control	RS-232C in/out, IR Remote Control, Keypad
Display orientationLandscapeSpeakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Auto brightness control	Ambient light sensor
Speakers12W x 2 built-inMountingVESA: 400 x 200mm; 8 holesPC Mounting: 100x200mm; 6 holes	Enclosure	Metal, industrial
Mounting VESA: 400 x 200mm; 8 holes PC Mounting: 100x200mm; 6 holes	Display orientation	Landscape
PC Mounting: 100x200mm; 6 holes	Speakers	12W x 2 built-in
	Mounting	VESA: 400 x 200mm; 8 holes
Video wall support up to 10v10 configuration and off schooluling		PC Mounting: 100x200mm; 6 holes
video wall support up to ToxTo configuration, On/on scriedding,	Features	Video wall support up to 10x10 configuration, on/off scheduling,
carrying handles, picture in picture (PiP)		
Optional accessories Flat wall mount, tilting wall mount, table stand	Optional accessories	· · · · · · · · · · · · · · · · · · ·
Warranty 3-year, 2-day advance replacement	Warranty	<u>`</u>








## For more information

To learn more about the Planar PS4200 by Planar Systems, call 503-748-1100 or visit www.planardigitalsignage.com.

# 39" 2.2" 992 mm 2.5" 57 mm 37" 63 mm 934 mm 21" 23" 42" 527 mm 1067 mm 585 mm 4.7"

#### back

front



## Standard inputs





Planar Systems, Inc. 1195 NW Compton Drive Beaverton, OR, 97006-1992, USA Toll Free +1-866-475-2627 www.planar.com

Planar is a trademark of Planar Systems, Inc. All other trade and service marks are the property of their holders.

Copyright @ 2011 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without written permission from Planar Systems, Inc. Information in this document is subject to change without notice.

side

120 mm