

Cachet Kiosk — JK2400 Series

POSIFLEX™

23.8" Screen

Wall-Mount
Option

Dual Kiosks
Back-to-Back Option

KEY FEATURES

- Windows:
 - Intel® Celeron® J6412
 - Intel® 11th Generation Core® i3 / i5 Series Processors
- Android:
 - Rockchip RK3399
- Bright, 23.8" PCAP, 1920 x 1080 display
- Thin, sleek profile
- Modular design
- Wallmount or with stand
- Single or dual-sided operation
- Includes monitor, CPU, 3" thermal printer, customer-facing camera, proximity sensor, service indicator, Wi-Fi, pedestal stand and base plate

* Some options may require assembly or installation at customer site. On-site installation services available for an additional charge.



Self Service for the Modern Retailer

Presenting a seamless blend of maximum functionality and sleek modern design, the JK2400 series stands as an ideal solution to cater to your business requirements while aesthetically complementing your work environment. Equipped with a 23.8" touch display, powered

by Intel's 11th generation Tiger Lake Core Processors, also available with Intel Elkhart Lake Celeron J6412 and Rockchip RK3399 high performance processor.

Cachet Kiosk — JK2400 Series

Specification	JK2410	JK2432	JK2452
Processor	Rockchip RK3399, Dual-core Cortex A72 up to 1.8GHz + Quad-core Cortex A53 up to 1.4GHz	Intel® Celeron® J6412, 1.5MB Cache, up to 2.0GHz	Intel® 11th Generation Core® i3 / i5 Series Processors
System Memory	4GB LPDDR4	1x slots 4GB DDR4 SO-DIMM [Max. 16GB]	1x slots 4GB DDR4 SO-DIMM [Max. 32GB]
Storage Device	32 GB eMMC + microSD slot x 1	M.2 SSD [SATA Signal Only] x 1	
TPM Support	N/A	TPM 2.0	
Intel vPro Support	N/A	N/A	Yes, with Core i5
Power Supply	12V/60W x 1 + 24V/60W x 1	12V/84W x 1 + 24V/60W x 1	
Supported OS	Android 9.0 / Android 10.0 with GMS	Windows 10 IoT Enterprise LTSC 64Bit	
Serial Port	RJ50 x 2, 5V/12V support on all COM ports	3, DB9 x 1 + RJ50 x 2, 5V/12V support on all COM ports	
Standard USB Port	6, USB 3.0 x 1 + USB 2.0 x 5	8, USB 3.0 x 2 + USB 2.0 x 6	8, USB 3.0 x 4 + USB 2.0 x 4
OTG USB	Micro-USB x 1	N/A	N/A
Display Port	HDMI x 1		
LAN Port	10/100 Mb x 1 ; 10/100/1000 Mb x 1	10/100/1000 Mb x 2	
Audio	Internal 3W speaker x 2		
Internal Expansion Slot	N/A	M.2 x 1	
Display & Touch			
LCD	23.8"		
Resolution	1920 x 1080		
Touch	True-Flat Projected Capacitive with Multi-touch support		
Physical Dimensions			
Dimensions (W x D x H inches)	23.7 x 23.7 x 68.5 (Single or dual sided); 15.7 x 5.49 x 38.9 (Wall-mounted)		
Weight (N. W. in lbs)	107.6 (Single sided); 134 (Dual sided); 45.19 (Wall-mounted)		
Environment			
Operating Condition	0°C - 40°C, 20%RH - 90%RH		
Storage Condition	-20°C - 70°C, 10%RH - 90%RH		
Included & Optional Components			
Proximity Sensor (included)	Range from 45cm ~ 80cm (for dark color objects); Range from 45cm ~ 150cm (for light color objects)		
Camera (included)	1MP wide angle camera		
Status Indicator (included)	RGB Color LED indicator		
WiFi (included)	USB Wireless Adapter		
Scanner	2D Barcode Imager		
EMV Payment Device Bracket Support	Custom bracket support for various EMV payment devices		
MSR	3 tracks ISO or JISII		
Fingerprint Sensor	Optical type		
RFID Reader	Support ISO/IEC 14443-A&B (MIFARE); JIS x 6319-4 (Felica); ISO/IEC 15693; NFC protocols - tag read/write (ISO/IEC-18902)		

** The product information and specifications are subject to change without prior notice.

*** Please contact your Posiflex sales representative as lead times may apply.