



Customer Pole Display



PD-7600 Series

- Graphic STN LCD (liquid crystal display) in blue background with white backlight.
- Stand alone Pole Display for POS application.
- Four-line display with 30 Arabic letters or 15 Chinese characters per line
- 240 by 64 dots for graphic display.
- Adequately sized characters for easy viewing (8.47 mm by 4.24 mm per digit).
- Long life and trouble free operation.
- Display contrast adjust buttons on front surface
- 15°, 30° and 45° adjustable viewing angles.
- Display frame can rotate horizontally 270° freely.
- Supports ESC/POS commands.
- Simple installation.
- Serial (RS232) interface.
- Case color choices: ivory, black

MODELS, LANGUAGES & CODE TABLES .

PD-7610: Simplified Chinese, GB-2312

PD-7620: Traditional Chinese, BIG-5

PD-7630: Arabic, Windows code page 01256 (with Arabic numerals addressed in <80> ~ <89> of code page 1)



PD-7200 Series

- Ergonomic designed.
- Stand-alone LCD pole display.
- Power and data on same connector when applied with Posiflex POS Terminal.
- Wide operating temperature range (0°C to 50°C).
- LCD viewing angle: 60 degrees vertically, 50 degrees horizontally.
- 3 User defined characters (16x16 dot).
- Character size 18.35x17.87 mm for 16x16 format.
- Character size 18.35x8.91 mm for 8x16 format.
- US-ASCII character (8x16 or 6x8 dot).
- Chinese GB or BIG-5 character (16x16 dot).
- RS-232C interface.
- Software self test.
- Command emulation modes include Epson, Noritake and IEE (for Chinese only).
- Display head 330° rotatable.
- Display head tilt angle 14.5°/ 30°.
- A rock switch on base for power ON/OFF if using AC power adaptor.

Multifunctional POS Peripherals

Customer Pole Display



PD-300 Series

- Two - line LCD display with 20 characters per line.
- Dark blue character with yellow green back-light.
- Easy viewing characters (6.0 mm by 9.66 mm).
- Display area 143 mm by 21 mm.
- Euro dollar sign supported in USA/European font table.
- Selectable command emulation modes including PST and EPSON command emulation modes.
- Long life, trouble free and user friendly operation.
- Composed of several members in the family for versatile applications as tabulated below.



PD-2600 Series

- Bright VFD (vacuum fluorescent display) with green or blue filter
- Rear mount Pole Display for Posiflex HT series hybrid terminals or PB series discrete systems or KS or FT series fan free touch POS terminals or TP series touch POS terminals
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03 mm by 5.25 mm).
- Long life and trouble free operation.
- 15°, 30° and 45° adjustable viewing angles.
- Total height 410 mm (Stand alone).
- Total height 392 mm (PD-2601 on base of HT and PB series).
- Total height 325 mm (PD-2602 on base of KS and TP series).
- Total height 375 mm (PD-2603 on base of FT series).
- Display frame can rotate horizontally 270° freely.
- Various command emulation modes selectable by DIP switch.
- Support 12 Code Pages of 128 characters each.
- Support 12 international character sets of 12 characters each.
- Simple installation.
- Selectable between Serial (RS232) interface model and USB interface model.
- Supports UPOS 1.8 and is WEPOS ready.
- Case color choices: ivory, black for HT terminals or black for FT, KS and TP terminals.



PD-2500 Series

- Fixed height Pole Display
- Ergonomic design
- Rigid mechanical structure
- Minimal footprint for ease of application on a crowded counterdesk
- Bright green or blue display by vacuum fluorescent device
- Large display character of size 11.25mm by 7.2mm
- Two lines by 20 characters per line
- Euro dollar sign supported
- Various command emulation modes selectable by DIP switch
- Intelligent auto-processing on hardware handshaking signals for both pass through and non-pass through application
- Improved heat dissipation
- Four tilt angle from 0° to 45° for best viewing effect
- Display head 330° rotatable
- Fixed total height 556mm above mounting plate
- USB interface model is also under development



PD-2300

- Bright vacuum fluorescent display.
- Two-line display with 20 characters per line.
- Adequately large characters for easy viewing (9.03 mm by 5.25 mm).
- Long life and trouble free operation.
- Generous base best for freely stand alone.
- Two adjustable viewing angles.
- Pole height adjustable.
- Display frame can slide horizontally and rotate 360°freely.
- Brightness adjustable by software.
- Simple installation.
- Direct interface connection with computers and peripherals.
- Selectable interface of Serial interface with pass through capability and USB interface.
- Multiple choices for power supply source.
- Support Euro Code Page.



PD-2100/2200 Series

- Bright vacuum fluorescent display.
- Two-line display with 20 characters per line.
- Large characters for easy viewing (11.25mm by 7.2 mm).
- Long life and trouble free operation.
- Secure construction with bumper best for screw on operation in PD-2100 Series. Generous base best for freely stand alone application in PD-2200 Series.
- Two adjustable viewing angles.
- Pole height adjustable.
- Display frame is horizontally slidable, and 360° rotatable freely.
- Brightness adjustable by software.
- Simple installation.
- Direct interface connection with computers and peripherals.
- Standard Serial interface for both series and with pass through capability for PD-2200 Series.
- Multiple choices for power supply source.
- Support Euro Code Page.



Posiflex Technologies, Inc.
6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.
Tel: 886 2 2299-1599 Fax: 886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

