RT-6015/6016

| Specification | RT-6015 | RT-6016 |
|------------------------------|--|----------------------------------|
| Processor | Intel Celeron 4305UE Intel Core i3-8145UE Intel Core i5-8365UE (Core i5 supports intel vPro and RAID) | |
| System Memory | DDR4 SO-DIMM x 2, max. 32 GB | |
| Storage Device | SATAIII ports x 2 | |
| TPM Support | TPM 2.0 | |
| OS Support | Windows 10 loT 64 bits | |
| Display & Touch | | |
| LCD | 15" TFT LCD with LED backlight | 15.6" TFT LCD with LED backlight |
| Resolution | 1024 x 768 | 1920 x 1080 |
| Touch | PCAP supporting multi-touch | |
| I/O & Expansion | | |
| Serial Port | DB9 x 1+ RJ50 x 2 | |
| Standard USB Port | USB 3.0 x 2 + USB 2.0 x 3 | |
| LAN Port | 10/100/1000 Mb x 1 | |
| Display Port | VGA (proprietary connector) x 1+ mini DP x 1 | |
| CR Port | 1, control 2 x cash drawer | |
| Audio | 2W speaker x 1 | |
| Internal Expansion Slot | M.2 x 1 for WiFi | |
| Physical Dimension | | |
| Dimension (W x D x H in mm) | 368 x 207 x 325 | 402 x 207 x 297 |
| Weight (N. W. in kg) | 5.4 | 5 |
| Environmental | | |
| Operating Condition | 0°C - 40°C, 20%RH - 90%RH | |
| Storage Condition | -20°C - 70°C, 10%RH - 90%RH | |
| Built-in Options | | |
| WiFi | M.2 WiFi/BT module | |
| Camera | 1MP wide angle camera | |
| AG Glass | Cannot coexist with built-in camera | |
| Expandable USB Module | USB 2.0 x 4 (USB 3.0 x 1 from the system will no longer be available with the USB extension module) | |
| Expandable PoweredUSB Module | $24V \times 1 + 12V \times 1$ [USB 3.0 x 1 from the system will no longer be available with the PoweredUSB extension module] | |
| UPS Battery Backup | UPS pack for RT Series | |
| Attachment Options | | |
| POS Monitor | 9.7"/10.1" TFT LCD display (touch/non-touch) | |
| Line Display | 20 rear-mount VFD customer line display x 2 | |

^{*}Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

^{*}Please refer to the website for more attachment options.



















Fax: +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller

<u>POSIFLEX</u>



RT-6015/6016

Make Your Business Look More Attractive

Fanless POS Terminal

^{*}The product information and specifications are subject to change without prior notice.











Slim & Stylish Look

With stylish, fluid contours for its base and true-flat design, the RT-6000 Series has 15" or 15.6" PCAP touch screen, and full suite of ports that are hidden in the clean rear cover. No screws can be found on its surface maintaining a neat and sleek look.

Patented Fanless Technology

The RT-6000 Series is built to perform in harsh environments that involve dust and liquid spills. Its patented fanless technology allows the unit to run silently and eliminates a potential point of failure, thus reducing service costs.



Fanless Technology



Dust Wa Resistant Resi



Water Resistant



Money Saving



Clean Cable Management

Advanced cable management design delivers a truly clutter-free station. The standard base can house the optional Powered USB or USB extension module, while the optional base integrates a UPS backup [RB-5000] for the event of a power failure.





Maintenance & Shipment with Ease

Rear cover can be removed easily and without tools, thus allowing for faster installation and serviceability. The unit can be shipped with line display or 2nd customer facing LCD display attached and folded, saving deployment time as well as shipping costs.