



YOUR VERSATILE PARTNER

TX 4200R

TX-4200R is specifically designed for retail applications. Its compact housing and VESA mounting capability allows TX-4200R to be placed anywhere around the counter, thus maximizing the useable counter space for the retailers. Three Powered USB ports (1 x 24V + 2 x 12V) allow the peripherals such as POS printer, electronic weight scale, or table scanner to be connected to the system without the need for the power adaptor, and once again, creating a clean and clutter-free counter space.

While TX-4200R is retail centrically designed, it still offers a wealth of connectivity options such as built-in mini-DisplayPort that allows for large size TV to be connected in Digital Signage application; five standard USB ports, two Serial ports, Parallel port and PS/2 port allow for further expansions, making TX-4200R a great all-around performer.

- Retail centric design
- Compact housing
- 1 x 24V + 2 x 12V Powered USB ports
- Mini-DisplayPort
- Mini-PCIe expansion slot
- VESA mounting

TX-4200R

System Configuration TX-4200R

Processor	Intel D2550 / 1.86GHz / 1M Cache (dual core)
System Memory	DDR3 1066MHz SO-DIMM x 1, max. 4GB, factory default 1GB
Storage Device	SATA Storage x 1, factory default 320GB HDD x 1
RAID	N/A
Power Supply	12V / 150W
OS support	Windows XP Pro / POSReady 2009 / Windows 7 / POSReady 7 / Linux per request

I/O & Expansion

Serial Port	2, DB9 x 2, optional COM3 / COM4 via conversion cable, 5V / 12V support on all COM ports
Parallel Port	1
Standard USB Port	6
Powered USB Port	24V x 1 + 12V x 2
LAN Port	10 / 100 / 1000 Mb x 1
Display Port	VGA x 1, optional 2nd VGA x 1, 12V support on both VGA ports for Posiflex monitors; DisplayPort x 1
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	Yes
UPS Port	N/A
Audio	Internal 2W speaker x 1 + Line-out
Internal Expansion Slot	mini-PCIe slot x 1

Built-in Device

Built-in WIFI	Optional mini-PCIe WIFI module
---------------	--------------------------------

Physical Dimension

Dimension (W x D x H in mm)	220 x 202 x 56
Weight (N. W. in kg)	1.31

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Design and Manufacturing In Taiwan by Posiflex Technology Inc.
The product information and specifications are subject to change without prior notice.

2013Q4C1

POSIFLEX Headquarters

Posiflex Technology Inc.
No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan
Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw
Fax : +886-2-2299-1819 Website : <http://www.posiflex.com.tw>

