

KEY FEATURES

- Intel® Atom™ 1.8GHz w/ 512KB Cache
- Maximum 4GB DDR3 RAM
- 15" TFT LC, 1024x768 resolution
- Resistive Advanced Touch Technology
- 4 USB Ports, Cash Drawer Port controls 2 drawers
- 160GB SATA HDD
- Integrated 3" Thermal Printer (150mm/sec)
- Integrated 2 or 3-Track MSR
- Die-cast aluminum chassis for heat diffusion
- Liquid and Splash Resistant
- Fan Free



XP3315 Series

About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of innovative excellence

Global presence

Over 30 patents for innovation

Two ISO 9001/ 14001 Certified Facilities





Space Saving ECR Replacement

The XP3315 Series terminal is a low cost All-in-One Electronic Cash Register (ECR) replacement, integrating Intel® Atom™ technology, Point of Service (POS) functionality, a 3" thermal printer, MSR and a tilt adjustable 15" TFT LCD with 1024x768 resolution advanced touch screen.

The compact form factor is ideal for space limited environments, especially where countertop area is at a premium. Being fan-free, the XP3315 reduces energy consumption, and eliminates a potential point of mechanical failure, reducing service costs.

For more information call 888.968.1668 today!

Specifications

SPECIFICATIONS		XP3315	AVAILABLE SERVICES
Processor	Intel® Atom™ D425 1.8GHz, 512KB Cache		<ul style="list-style-type: none">• Standard and Extended Warranty Extend your depot warranty up to 5 years.• Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.• OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process.• Regional Repair Depots Three regional depots assure fast turn-around time on repairs.• Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs.• Installation Services Let our nationwide network of experts stage and install your equipment.• OEM Design and Integration Our Product Development Team helps design equipment, for custom hardware applications.
System Memory	DDR3 800 MHz, SO-DIMM socket x 1 (1GB Default)		
Maximum Memory	3GB with 32-Bit OS, 4GB with 64-bit OS		
Power Supply	12V DC Power adaptor, 120W		
Storage Device	2.5" SATA 160GB HDD or SSD Kit (optional)		
Supported OS	POSReady / WinXP Pro / Win7 Pro (32 or 64 bit) / Linux		
DISPLAY			
LCD	15" TFT LCD, 1024x768		
Touch Function	5-Wire Resistive, USB Interface		
Brightness Control	Digital Push Button		
Tilt Adjustment	14° to 55°		
PHYSICAL DIMENSIONS			
Dimensions (WxDxH)	14.76" x 15.20" x 15.55"		
Weight (Pounds)	15 lbs		
CONNECTIVITY			
LAN Port	10/100/1000 Base-T Ethernet		
Serial Port	DB9 x 3, RJ-50 x 1 (5V/12V support on COM1/COM2/COM3/COM4)		
Backup Battery	Yes, Battery (optional)		
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD Monitor		
CR Port	CR x 1 (Controls 2 drawers)		
Standard USB Port(s)	4		
PRINTER AND MSR			
Auto Cutter 3" Printer	Thermal Printing at 150mm / second, 80mm paper width		
Magnetic Stripe Reader	2 or 3-Track MSR		
PERIPHERALS			
<div>Rear Display - PD3300 2x20 Character LCD</div> <div></div>	<div>Rear Display - PD2606 2 x 20 Character VFD*</div> <div></div>	<div>Rear Pole Display - PD2605 2 x 20 Character VFD*</div> <div></div>	<div>Rear Touch Monitor - TM2212 12" LCD Display w/ Resistive Touch</div> <div></div>

*Vacuum Fluorescent Display

See www.posiflexusa.com for a complete line of peripherals

POSIFLEX™
Be the Pioneer, Be the Leader
30689 Huntwood Avenue
Hayward, CA 94544
Toll-free: 888.968.1668
Phone: 510.429.7097
Fax: 510.475.0982
E-mail: sales@posiflexusa.com
www.posiflexusa.com

