



# **KEY FEATURES**

- 15" (XT3815) or 17" (XT3817) models
- Intel<sup>®</sup> Celeron<sup>™</sup> J1900 / 2.0GHz
- 4GB DDR3L memory (8GB maximum)
- Projected Capacitive touch
- Fan Free
- Spill and dust resistant
- USB 3.0 support
- Digital Brightness Control
- VESA mount capability
- Slim, folding base design
- Optional Solid State Drive and WiFi
- Optional Upgrade Kits
  - Powered USB Kit
    - (1) 24V USB 2.0 Port and (3) 12V USB 2.0 Ports
    - Powered USB base can house power adapter and backup battery with 150W power supply
    - 8-Port USB Hub Kit
      - (8) port USB hub with 150W power supply

# **Performance at Exceptional Value**

XT3815

The XT3800 Series is a cost-effective workhorse, ideal for environments where cost is a factor, but performance cannot be compromised either. Backed by field-tested reliability, the spill and dust resistant XT3800 Series inherits the long legacy of quality that only Posiflex can deliver.

XT3817

(black bezel)

The XT3800 Series base conveniently folds and configures to an optimal angle and space for various types of environments. The low-profile design fits in the tightest of spaces, reducing shipping costs up to 40%. With this sleekly designed exterior comes the Intel® Celeron<sup>™</sup> 2.0GHz power to run many applications for hospitality, retail, healthcare and more.

The XT3800 Series features an Intel® Celeron<sup>™</sup> J1900 / 2.0GHz, 4GB standard DDR3L RAM (8 GB maximum) and a 15" or 17" projected capacitive touch TFT LCD touch screen terminal. Along with a rich array of connectivity features are options for a mini-PCle slot for WiFi and VESA wall mount bracket.

#### **About Posiflex**

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

| Specifications         | XT3800 Series   |  |
|------------------------|---|--|
| Processor              | Intel <sup>®</sup> Celeron <sup>™</sup> J1900 / 2.0GHz                      |  |
| System Memory          | DDR3L SO-DIMM x 1, max. 8GB, factory default 4GB                            |  |
| Storage Device         | 320GB HDD<br>SSD Available  |  |
| Supported OS           | POSReady 7 / Windows 7<br>Professional / Windows Embedded 8.1 Industry      |  |
| Touch                  | Projected Capacitive  |  |
| Physical Dimensions    |   |  |
| Dimensions (WxDxH) in. | XT3815: 14.6 x 12.5 x 9.9 / XT3817: 16 x 13 x 14.5                          |  |
| Display                | 15" (1024 x 768) or 17" (1280 x 1024) LED-backlit TFT LCD                   |  |
| Weight (lbs)           | XT3815: 12.3 / XT3817: 16.0   |  |
| Connectivity           |   |  |
| LAN Port               | 1 x Gigabit LAN Port  |  |
| Serial Port            | 1 x RJ-50 Serial<br>3 x DB9 Serial  |  |
| VGA Port               | 1 x VGA Port  |  |
| USB 2.0 Port           | XT3815: 6x - 5 on I/O Panel; 1 on Power Side<br>XT3817: 6x - 6 on I/O Panel |  |
| USB 3.0 Port           | 1 x on I/O Panel  |  |
| 12v Battery port       | 1 x Proprietary port used with the RB2000                                   |  |
| Mini-PCle slot         | 1   |  |
| CR PORT                | 1 x (Controls 2 Drawers)<br>Dual Independent Sensor<br>COM1/COM5 Select     |  |

## **Options**

### SSD

Parallel Port with optional extension cable

WB-5000 wall mount bracket

#### WiFi

| Peripherals  |  |
|--------------|--|
| WB5000       | Wall mount bracket   |
| Upgrade Kits | Powered USB Upgrade Kit<br>- (1) 24V USB 2.0 Port plus (3) 12V USB 2.0 Ports with 150W power supply<br>8-Port USB Hub Kit<br>- (8) port USB hub with 150W power supply |
| PD2605X00FEP | 2X20 VFD rear-mount pole display   |
| PD2605W00FEP | 2X20 VFD rear-mount pole display   |
| PD2608UE011  | 2X20 VFD rear-mount customer display   |
| RB2000       | Backup battery   |
| SA105100     | 3 track encryption capable without finger print reader   |
| SA30520100   | 3 track encryption capable with finger print reader  |
| LM3010000    | 9.7" rear-mount secondary display  |
| LM3015000    | 15" rear-mount secondary display   |

\*\* The product information and specifications are subject to change without prior notice.



Touch Screen Terminals & Tablets | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

Rev. 062817

# **Available Services**

- Standard and Extended Warranty Extend your depot warranty up to 5 years.
- Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- **OnSite Service** Expert technicians will efficiently handle the complete equipment swap and return process.
- **Regional Repair Depots** Three regional depots assure fast turn-around time on repairs.
- **Post Warranty Support** Spare parts, in addition to a flat rate repair program, for post warranty needs.
- Installation Services
  Let our nationwide network of experts
  stage and install your equipment.
- OEM Design and Integration
  Our Product Development Team
  helps design equipment, for custom
  hardware applications.



Posiflex Business Machines, Inc. 30689 Huntwood Ave. Hayward, CA 94544 P: 888-968-1668 F: 510-475-0982 sales.department@posiflexusa.com www.posiflexusa.com

(intel)

ORACLE