





XT4015

KEY FEATURES

- Scalable choice of three powerful CPUs
- 4GB DDR3 memory (16GB maximum)
- Bezel-Free Resistive or Projective Capacitive
- Digital Brightness Control
- New, sleek, folding base design
- Slimmer overall footprint
- Dual Gigabit LAN
- New, sleek design
- Optional Solid State Drive
- VESA Mount and WiFi optional capability

About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

Flexible. Powerful. Elegant.

The XT4015 brings space-saving design to the Posiflex family with a terminal that folds and configures to an optimal angle and space. The low-profile design fits in the tightest of spaces, reducing shipping costs up to 40%.

With this sleekly designed exterior comes the power needed to run and secure most applications for hospitality, retail, health care and more. XT4015 offers a choice of three powerful Intel™ processors, the G540 2.5 GHz, Core i3-3220, 3.3GHz or the Core i5-3550s, 3.7 GHz to give you the choice of the price / performance you require. To secure valuable data, the XT4015 optionally offers RAID 1 (disk mirroring).

The XT4015's bezel-free projective capacitive or resistive touch screen terminal comes standard with 4GB DDR3 RAM, and can be upgraded up to 16GB. Along with a rich array of connectivity features is the option for a mini-PCIe slot for WiFi and a VESA wall-mount bracket.

Specifications	XT4015	
Processor	Intel G540 CPU, 2.5GHz / 2M Cache; Intel Core i3-3220, 3.3GHz / 3M Cache; Intel Core i5-3550s CPU, 3.7GHz / 3M Cache	
System Memory	DDR3 1333/1600MHz, SO-DIMM x 2, max 16GB, factory default 4GB	
Storage Device	SATA Storage x 2, factory default 320GB HDD x 1	
Supported OS	POSReady 2009, POSReady 7, Windows XP, Windows 7, Linux (driver availability only)	
Touch	Bezel-free Resistive or Projective Capacitive touch	
RAID 1	Disk Mirroring	

Physical Dimensions		
Dimensions (WxDxH) in.	14.6" x 12.6" x 9.9"	
Display	15" LCD with 1024x768 resolution	
Weight (lbs)	13.5	

Connectivity	
LAN Port	2 x 10/100/1000 LAN
Serial Port	3 x DB9; 1 x RJ50
VGA PORT	1
Standard USB Port	5 (4 on I/O panel, 1 on side)
Mini-PCIe slot	Optional
CR PORT	1 (controls 2 devices)

Options

SSD

Parallel Port with optional extension cable

WB-5000 wall mount bracket

WiFi

Peripherals	
MSR w/ Optional Finger Print	SA100, SA300
Pole Display	PD2604 (Rear Mount)
Secondary Monitor	12" LM2312
Printer	PP9000
Cash Drawer	CR6300, CR3100

^{**} The product information and specifications are subject to change without prior notice.







PP9000 USB + Optional Serial, Parallel, LAN or Wireless



CR3100 Adjustable Coin Slot 15.7"W x 16.3"D x 3.5"H

Available Services

- Standard and Extended Warranty Extend your depot warranty up to 5 years.
- Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex.
- OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process.
- Regional Repair Depots Three regional depots assure fast turn-around time on repairs.
- Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs.
- Installation Services Let our nationwide network of experts stage and install your equipment.
- **OEM Design and Integration Our Product Development** Team helps design equipment, for custom hardware applications.

















