

XT6315 Series

POSIFLEX™

KEY FEATURES

- Intel® Skylake Core™ i5 6500TE CPU
2.3 GHz / 3.3 GHz [Burst]
- DDR4 SO-DIMM x 2 memory
(32GB maximum)
- Projected Capacitive touch
- Sleek, folding base design
- Slimmer overall footprint
- Optional Upgrade Kits
 - Powered USB Kit
 - (1) 24V USB 2.0 Port and
(3) 12V USB 2.0 Ports
 - Powered USB base can house
power adapter and backup battery
with 150W power supply
 - Powered USB and USB Hub
Expansion Kit
 - (8) port USB hub with
150W power supply
 - (1) 24V USB2.0 Port and
(8) 5V USB 2.0 Ports



Power and Performance

The XT6315 uses powerful embedded Intel® processors supported by Windows Embedded operating systems. This combination of Intel and Microsoft assures long-term support and availability, critical for long-term location rollouts.

To eliminate additional peripheral power bricks and cable clutter, the XT6315 has an optional Powered USB upgrade kit.

The high performance XT6315 has a collapsible folding base configurable for maximum viewing

flexibility and unparalleled flexibility.

A vibrant projected capacitive touch screen comes standard on the XT6315, offering 10-point multi-touch capability, a bezel-free 100% flat, scratch-resistant surface.

XT6315 Series





Specifications

Processor Options	Intel® Skylake Core™ i3 6100TE CPU, 2.7 GHz Intel® Skylake Core™ i5 6500TE CPU, 2.3 GHz / 3.3 GHz [Burst]
Memory	DDR4 SO-DIMM x 2, max 32 GB
Display	15" [1024 x 768]
Touch	Projected Capacitive (10 point touch)
Storage	SATA connector x 2
Operating Systems	POS Ready 7 / Windows Embedded 8.1 64bit / Windows 10 IoT 64bit
Dimensions (WxDxH) in.	14.6 x 12.5 x 9.9
Weight (lbs)	12.9
Serial Port	6, 4 on I/O plate (2 x DB9 + 2 x RJ45) + 2 via optional converter cable from service window, 5V support on all COM ports, 12V support on COM1 - 4 (all converter cables are optional)
Parallel Port	Optional via conversion cable
Standard USB Port	6, 4 x USB 3.0 + 2 x USB 2.0
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8E base
LAN Port	10 / 100 / 1000 Mb x 2
Display Port(s)	VGA x 1 + mini-HDMI x 1, 12V support on VGA port for Posiflex monitors
CR Port	1 Port (Controls 2 Drawers via optional Y-cable)
UPS Port	Yes, battery optional
Audio	Internal 2W speaker x 1 + Mic-in/Line-out
Internal Expansion Slot	M.2 slot x 1

Optional Accessories

WB5000	Wall mount bracket
Upgrade Kits	Powered USB Upgrade Kit - (1) 24V USB 2.0 Port plus (3) 12V USB 2.0 Ports with 150W power supply 8-Port USB Hub Kit - (8) port USB hub with 150W power supply
PD2605X00FEP	2X20 VFD rear-mount pole display
PD2605W00FEP	2X20 VFD rear-mount pole display
PD2608UE011	2X20 VFD rear-mount customer display
RB2000	Backup battery
SA105100	3 track encryption capable without finger print reader
SA30520100	3 track encryption capable with finger print reader
LM3010000	9.7" rear-mount secondary display
LM3015000	15" rear-mount secondary display

** The product information and specifications are subject to change without prior notice.

SECONDARY DISPLAYS	MAGNETIC STRIPE READERS	CASH DRAWERS	RECEIPT PRINTER
 PD2605 PD2608 LM3010 Bezel-Free Rear Mount	 SA100 SA300 Optional: Fingerprint Reader	 CR3100 Adjustable Coin Slot CR6300 Fixed Coin Slot	 PP9000



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

Rev. 050820



POSIFLEX™

Posiflex Business Machines, Inc.

30689 Huntwood Ave.

Hayward, CA 94544

P: 888-968-1668

F: 510-475-0982

sales.department@posiflexusa.com

www.posiflexusa.com