

XT6300 Series

POSIFLEX™



XT6317 (17" Display)

XT6315 (15" Display)



KEY FEATURES

- Intel® Celeron G3900TE, 2.30 GHz, 2M Cache
- Intel® Core i3-6100TE, 2.70 GHz, 4M Cache
- Intel® Core i5-6500TE, up to 3.30 GHz, 6M Cache
- 2x slots 4GB DDR4 SO-DIMM (Max. 32GB) 2666 Mhz 1.2v
- Projected Capacitive touch
- Sleek, folding base design
- Slimmer overall footprint
- Optional Upgrade Kits
 - Powered USB Kit
 - (1) 24V USB 2.0 Port and (3) 12V USB 2.0 Ports
 - Powered USB base can house power adapter and backup battery with 150W power supply
 - Powered USB and USB Hub Expansion Kit
 - (8) port USB hub with 150W power supply
 - (1) 24V USB2.0 Port and (8) 5V USB 2.0 Ports

Power and Performance

The XT6300 Series uses powerful embedded Intel® processors supported by Windows Embedded operating systems. This combination of Intel and Microsoft assures long-term support and availability, critical for long-term location rollouts.

To eliminate additional peripheral power bricks and cable clutter, the XT6300 Series has an optional Powered USB upgrade kit.

The high performance XT6300 Series—which includes 15" or 17" model—has a collapsible folding base configurable for maximum viewing

flexibility and unparalleled flexibility. A vibrant projected capacitive touch screen comes standard on the XT6300 Series, offering 10-point multi-touch capability, a bezel-free 100% flat, scratch-resistant surface.

XT6300 Series

Specifications	XT6315	XT6317
Processor Options	Intel® Celeron G3900TE, 2.30 GHz, 2M Cache; Intel® Core i3-6100TE, 2.70 GHz, 4M Cache; Intel® Core i5-6500TE, up to 3.30 GHz, 6M Cache	
System Memory	2x slots 4GB DDR4 SO-DIMM (Max. 32GB) 2666 Mhz 1.2v	
Storage Device	128GB SSD or higher. Up to two drives.	
Supported OS	Windows POSReady 7 / Windows 10 IoT Enterprise	
Passive Cooling	Fanless	
Touch	True-Flat Projected Capacitive with Multi-touch support	
Physical Dimensions		
Dimensions (WxDxH) in.	14.6 x 12.5 x 9.9	15.9 x 13.9 x 9.9
Display	15" (1024 x 768)	17" (1280 x 1024)
Weight (lbs)	12.9	14.3
Connectivity		
LAN Port	2 x Gigabit LAN	
Serial Port	2 x DB9 Serial; 2 x RJ-50 Serial (5v/12v support on all COM ports)	
Display Port	1 x VGA Port (12v Support for Posiflex monitors); 1 x mini-HDMI	1 x VGA Port (12v Support for Posiflex monitors); 1 x HDMI
USB Port	2 x USB 2.0; 4 x USB 3.0	4 x USB 2.0; 4 x USB 3.0
PoweredUSB Port	Optional 24V x 1 + 12V x 3 via GEN8E base	
12v Battery Port	1 x Proprietary port used with RB2000	
Mini-PCIe Slot	1 x M.2 slot	
CR Port	1 Port (Controls 2 Drawers); Dual Independent Open Sensor; COM1/COM5 Select	
Optional Accessories		
SSD	SSD	
Parallel Port	Parallel Port with optional extension cable	
Wall Mount	WB-5000 wall mount bracket	
WiFi/Bluetooth	802.11 ac, Dual Band 2.4GHz / 5GHz; BT 4.2	
Upgrade Kits	Powered USB Upgrade Kit - (1) 24V USB 2.0 Port plus (3) 12V USB 2.0 Ports with 150W power supply 8-Port USB Hub Kit - (8) port USB hub with 150W power supply	

** The product information and specifications are subject to change without prior notice.



SECONDARY DISPLAYS	MAGNETIC STRIPE READERS	CASH DRAWERS	RECEIPT PRINTER
 PD2605 PD2608 LM3010 Bezel-Free Rear Mount	 SA100 SA300 Optional: Fingerprint Reader	 CR3100 Adjustable Coin Slot CR6300 Fixed Coin Slot	 PP9000

POSIFLEX™

Posiflex Business Machines, Inc.
 30689 Huntwood Ave.
 Hayward, CA 94544
 P: 888-968-1668
 F: 510-475-0982
sales.department@posiflexusa.com
www.posiflexusa.com



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays