

XT7315 Series

POSIFLEX™

KEY FEATURES

- A Wide Selection of Processors
 - Intel® Celeron® G4900T, 2.90 GHz
 - Intel® Pentium® G5400T, 3.10 GHz
 - Intel® Core™ i3-8100T, 3.10GHz
 - Intel® Core™ i5-8500T, 3.50GHz
- 2x slots 4GB DDR4 SO-DIMM (Max. 32GB) 2666 Mhz 1.2v
- Projected Capacitive touch
- Sleek, folding base design
- Slimmer overall footprint
- Optional Upgrade Kits
 - Powered USB Kit
 - (1) 24V USB 2.0 Port and (3) 12V USB 2.0 Ports
 - Powered USB base can house power adapter and backup battery with 150W power supply
 - Powered USB and USB Hub Expansion Kit
 - (8) port USB hub with 150W power supply
 - (1) 24V USB2.0 Port and (8) 5V USB 2.0 Ports



Power and Performance

The XT7315 is part of the XT Series, built with an elegant yet practical design. Every curve and detail of the XT7315 line is carefully thought out to make itself one of the most visually desirable terminals in the market.

With the XT7315, you get a wide range of CPU options to fit your requirements. And, with a patented foldable base, users can adjust the screen to a height and angle of their choice, providing unparalleled flexibility.

With its fanless design, the XT7315 requires less maintenance and can run silently, which is ideally suited for high-end boutique stores or hospital environments.

XT7315 Series

Specifications

Processor Options	Intel® Celeron® G4900T, 2M Cache, 2.90 GHz Intel® Pentium® G5400T, 4M Cache, 3.10 GHz Intel® Core™ i3-8100T, 6M Cache, 3.10GHz Intel® Core™ i5-8500T, 9M Cache, 3.50GHz
System Memory	2x slots 4GB DDR4 SO-DIMM (Max. 32GB) 2666 Mhz 1.2v
TPM Support	TPM 2.0
Storage Device	128GB SSD or higher. Up to two drives.
Supported OS	Windows 10 IoT Enterprise
Passive Cooling	Fanless
Touch	True-Flat Projected Capacitive with Multi-touch support

Physical Dimensions

Dimensions (WxDxH) in.	14.6 x 12.6 x 9.9
Display	15" (1024 x 768)
Weight (lbs)	12.9

Connectivity

LAN Port	2 x Gigabit LAN
Serial Port	2 x DB9 Serial; 2 x RJ-50 Serial (5v/ 12v support on all COM ports)
Display Port	1x VGA Port (12v Support for Posiflex monitors) + 1 x mini-HDMI
USB Port	2 x USB 2.0; 4 x USB 3.0
12v Battery Port	1 x Proprietary port used with RB2000
Mini-PCIe Slot	1 x M.2 slot
CR Port	1 Port (Controls 2 Drawers); Dual Independent Open Sensor; COM1/COM5 Select

Options

SSD	SSD
Parallel Port	Parallel Port with optional extension cable
Wall Mount	WB-5000 wall mount bracket
VESA Mount	100mm
WiFi/Bluetooth	802.11 ac, Dual Band 2.4GHz / 5GHz; BT 4.2
Powered USB	1 x 24V + 3 x 12V (via GEN8E base)

** The product information and specifications are subject to change without prior notice.



SECONDARY DISPLAYS	MAGNETIC STRIPE READERS	CASH DRAWERS	RECEIPT PRINTER
<p>PD2605 PD2608 LM3010 Bezel-Free Rear Mount</p>	<p>SA100 SA300 Optional: Fingerprint Reader</p>	<p>CR3100 Adjustable Coin Slot CR6300 Fixed Coin Slot</p>	<p>PP9000</p>



Posiflex designs, engineers and manufactures:

Touch Screen Terminals | Tablets | Kiosks | Printers | Magnetic Stripe Readers | Cash Drawers | Rear/Pole Displays

Rev. 121621

POSIFLEX™

Posiflex Business Machines, Inc.

30689 Huntwood Ave.

Hayward, CA 94544

P: 888-968-1668

F: 510-475-0982

sales.department@posiflexusa.com

www.posiflexusa.com