



RUGGED DESIGN

400,000 page per month duty cycle

HIGH SPEED

32 pages per minute

EASE OF USE

Fast supply item replacement

WIDE RANGE OF OPTIONS

Cabinet stand, power assist stacker, full power stacker, cutter, MICR

NO FORMS WASTE

Leading edge self alignment, reversible drive system

DESIGNED FOR MISSION CRITICAL APPLICATIONS

Printronix, the world leader in continuous form laser printers, offers global reach in sales, support and logistics that meets the needs of customers regardless of company size or geographic location. Extending this leadership further is the L7032. This printer delivers a powerful combination of speed, ease of use, small foot print, high workload, flexible media handling and affordability. Rated at 32 pages per minute and up to 400,000 pages per month, this printer is ideal for use in distribution, supply chain and manufacturing applications.

MAXIMUM UPTIME – MINIMUM HASSLE

Designed specifically for high volume mission critical applications, each consumable or service item delivers extended life to minimize the number of user interventions. When items do need refreshing, they can be replaced in minutes without tools or special training. This long life coupled with extreme ease of use creates a print solution that reliably delivers high volume throughput.

CONTINUOUS FORMS ADVANTAGE

The L7032 offers laser printing's high quality imaging with the ability to handle challenging forms not possible with cut sheet feeders. A straight paper path and positive engagement tractor drive system ensures that heavy card stock, labels, tags or massive print jobs run jam and misalignment free. In addition, continuous forms printing offers the advantage of handling very large input and output, while naturally keeping forms together and in sequence.



PRINTRONIX®

GLOBAL PRINTING...ENABLED.

SPEED

| | |
|------------------------|------------------|
| Pages-Letter Landscape | 32 ppm |
| Pages-Letter Portrait | 25 ppm |
| Lines Speed | 1650 lpm @ 6 LPI |
| Plot Speed | 4.58 ips |

MEMORY

| | |
|----------|------------|
| Standard | 12MB RAM |
| | 16MB Flash |

FIRST PAGE SPEED

| | |
|-----------------------|--------------|
| Initial From Power Up | <200 seconds |
| From Standby | <45 seconds |
| Ready State | <20 seconds |

TECHNOLOGY

| | |
|------------|-------------------|
| Imaging | Laser |
| Fusing | Heat and pressure |
| Drum Type | OPC |
| Paper Path | Straight through |

RESOLUTION

| | |
|---------------------|---------------|
| Standard | 600 x 600 dpi |
| Software Selectable | 300 x 300 dpi |

WORKLOAD

| | |
|---------------------|---|
| Monthly Workload | 400,000 pages (8.5" x 11" landscape) |
| Maximum Total Pages | 24,000,000 pages (8.5" x 11" landscape) |
| Design Life | 5 years |

REPLACEMENT INTERVALS*

| | |
|-----------------------|----------------------------|
| Toner | 32,000 pages @ 4% coverage |
| Waste Toner Container | 64,000 pages |
| Felt Wiper | 64,000 pages |
| OPC Cartridge | 400,000 pages |
| Developer Unit | 800,000 pages |
| Fuser Unit | 800,000 pages |

*All items are end user replaceable

MEDIA TYPES

| | |
|-----------|---|
| Type | Pin fed continuous plain paper, label stock, card stock and tag stock |
| Weight | 16 lbs to 42 lbs bond 33-116 lbs index 36 – 129 tag & label |
| Thickness | 0.014" max |
| Width | 15.25" maximum edge-to-edge 5.9" minimum hole-to-hole |
| Length | 3" min to 33" max |

PRINTABLE AREA

| | |
|--------------|---|
| Print Width | 13.6" |
| Print Height | Up to full form length - no margin required |

INTERFACES

| | |
|----------|--------------------------|
| Parallel | IEEE-1284 (standard) |
| Ethernet | 10/100 Base T (standard) |

SYSTEM CONNECTIVITY

| | |
|-----------|--|
| Emulation | PCL5e (standard) PGL (optional) VGL (optional) |
| Drivers | Windows 2000/NT/XP/VISTA |

PRINTER FEATURES

| | |
|----------|---|
| Optional | Cabinet stand Power assist stacker Full power stacker Cutter MICR toner |
|----------|---|

POWER

| | |
|------------------------|---|
| Consumption | 1.3 kW – printing 700 W – during printing 70 W – standby mode |
| Line voltage (+/- 10%) | 100 – 120 VAC (standard) 200 – 240 VAC (optional) |
| Line frequency | 50/60 Hz |

ENVIRONMENTAL

| | |
|-----------------------|----------------------------|
| Operating Temperature | 50° – 90° F |
| Operating Humidity | 20 – 80% Relative Humidity |
| Maximum Altitude | 7,500 feet |
| Acoustic Noise | <55 dBA |

DIMENSIONS

| | Printer | W/ Cabinet | W/ Power Assist Stacker | W/ Full Power Stacker |
|-----------------|---------|------------|-------------------------|-----------------------|
| Height | 16.5" | 48" | 48" | 46" |
| Width | 24" | 40" | 63" | 39" |
| Depth | 24" | 25" | 25" | 25" |
| Shipping Weight | 134 lbs | 50 lbs | 65 lbs | 133 lbs |

Dimensions include the printer and option
Weights are individual items

GENUINE PRINTRONIX SUPPLIES

Choosing the right supplies is critical for the life of the printer, print quality, image durability and total cost of operation. Protect your investment with Genuine Printronix Supplies. The Printronix support staff has all the technical expertise, resources and familiarity with these supplies to help keep your mission critical applications flowing.

GENUINE
PRINTRONIX
SUPPLIES