ProGlove MARK Display

WIRELESS COMMUNICATION BLUETOOTH LOW ENERGY

| BLUETOOTH RADIO | Supports Bluetooth Low Energy 4.0, 4.1, 4.2, 5.0 |
|--------------------|---|
| TRANSMISSION RANGE | Free field: 40 m (131 ft)** |
| | Indoor: 10-20 m (33-66 ft)** |
| | **may decrease in industrial environments (e.g. due to walls, metal |
| | shelving, machines) |

BARCODE DECODING CAPABILITIES

| 1D | Auto decodes all standard 1D codes including GS1 DataBar linear codes et al. |
|--------|--|
| 2D | PDF417, MicroPDF417, Data matrix, QR Code, Micro QR Code, Aztec, MaxiCode, et al. |
| POSTAL | US PostNet, US Planet, UK Postal, Australia Postal, Japan Postal, Dutch Postal (KIX) et al. |

DISPLAY

| DISPLAY | E-PAPER DISPLAY |
|------------|-------------------------------------|
| SIZE | 1.54 inch |
| RESOLUTION | 200 x 200 pixel resolution, 188 Dpi |

ELECTRICAL PROPERTIES

| BATTERY | 670 mAh, Lithium polymer (rechargeable) |
|------------------------|--|
| CHARGING TIME | 2 hours with ProGlove Charging Station |
| OPERATING TIME / SCANS | approx. 6000 scans depending on the application and environmental conditions |

MECHANICAL PROPERTIES

| DIMENSIONS | 50 x 45 x 18 mm (1.47 x 1.77 x 0.7 in) |
|------------|--|
| WEIGHT | 48 g (1.7 oz) |

ENVIRONMENTAL CONDITIONS

| DROP RESISTANCE | 50 drops from 2 m (6.5 ft) onto concrete |
|-------------------------|--|
| TUMBLES | 500 tumbles from 1 m |
| PROTECTION AGAINST DUST | IP 54 |
| AND WATER | |
| TEMPERATURE | Operating Temperature: 0°C - 45°C (32°F – 113°F) |
| | Charging Temperature: 5°C - 40°C (41°F – 104°F) |
| | Storage Temperature: -20°C - 60°C (-4°F – 140°F) |
| HUMIDITY | 5% - 95% non condensing |
| ELECTROSTATIC DISCHARGE | ±19kVdc air discharge |
| (ESD) | ±17kVdc contact discharge |

INTERFACES

| | ANDROID | Insight Mobile (App/SDK) |
|---|---------|--------------------------|
| | IOS | ProGlove iOS SDK |
| ĺ | USB | ProGlove Gateway |

SCANNER PROPERTIES

| READING FIELD OF VIEW | horizontal: 31°, vertical 23° |
|-----------------------|-------------------------------|
| SKEW, PITCH & ROLL | Skew tolerance: ±60° |
| | Pitch tolerance: ±60° |
| | Roll tolerance: 360° |
| AMBIENT LIGHT | 0 - 96,900 lux |
| AIMER | 650 nm, 1 mW |

UTILITIES & ACCESSORIES

| CONFIGURATION & DEVICE MANAGEMENT | https://insight.proglove.com |
|-----------------------------------|---|
| DEVELOPER DOCUMENTATION | https://developers.proglove.com |
| ANDROID INTEGRATION | Insight Mobile: Provides a full featured integration for Android enterprise applications. |
| GATEWAY INTEGRATION | ProGlove Gateway: Hardware connector to enable the full capabilities of the ProGlove Ecosystem via USB-Interface. |
| TRIGGER | Scanner can be triggered only with ProGlove wearables (REEL, Index- Trigger et al.) |

SCAN RANGES

Minimum distance determined by symbol length, scan-angle and environmental conditions

MID RANGE

| 5 mil (0.127 mm) code 128 | 7.4 in./18.8 cm to 16.0 in./40.6 cm |
|--|--|
| 5 mil (0.127 mm) PDF417 | 8.1 in./20.6 cm to 13.1 in./33.3 cm |
| 10 mil (0.254 mm) DataMatrix | 7.0 in./17.8 cm to 17.0 in./43.2 cm |
| Example: A 10 mil DataMatrix symbol, which can | |
| carry 25 alphanumeric characters, has a size of 4.57 | |
| mm * 4.57 mm | |
| 100% UPCA | 2.3 in./5.8 cm to 38.0 in./96.5 cm |
| 20 mil (0.508 mm) code 39 | 2.1 in./5.3 cm to 54.0 in./137.2 cm |
| 100 mil (2.54 mm) code 39 | 11.0 in./ 27.9 cm to 172.0 in./ 436.9 cm |

WARRANTY & SLA

| WARRANTY | 12 months factory warranty |
|---------------|--|
| PROGLOVE CARE | 36 and 60 months maintenance contracts available. For more |
| | information please contact your ProGlove representative or visit |
| | https://proglove.com |

SAFETY & REGULATORY

| DAILLI GIRLOGLATORI | |
|---|---|
| RADIO AND ELECTROMAGNETIC COMPATIBILITY | EU: 2014/53/EU Radio Equipment Directive (RED) FCC ID: 2AOJL-MARK-2 IC: 23450-MARK2 |
| ELECTRICAL SAFETY | EU: acc. to 2014/53/EU Radio Equipment Directive (RED) EN 62368-1:2014 / A11: 2017 INTERNATIONAL: IEC 62368-1:2014 US/CD: UL 62368-1, 2 nd Ed, 2014-12-01 and CAN/CSA C22.2 No. 62368-1-14 |
| LASER CLASSIFICATION | According to EN 60825-1: 2014 and IEC 60825-1 (Ed. 3.0) Laser class 2 device. Caution Laser Radiation - Do not stare into beam. |
| ENVIRONMENTAL | RoHS Directive 2011/65/EU; Amendment 2015/863, REACH SVHC 1907/2006 |

COUNTRY CERTIFICATION

Regulatory markings are affixed to the device, indicating that the radio modules are approved for use in the following regions: European Economic Area*, Canada, United States of America, United Mexican States

 $\label{eq:decomposition} Detailed information on the regulatory markings can be found in the Declaration of Conformity (DoC) at \\ \underline{www.proglove.com}$

*CE is valid in the European Economic Area and additional countries: Austria, Belgium, Bulgaria, Croatia, Republic of Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, United Kingdom, Iceland, Liechtenstein, Switzerland and Norway.