

Specifications

		SCC-B2305	SCC-B2305P	SCC-B2005P
Camera Type Image	Color	Color		
	Device	Super-HAD PS CCD		
	Size	1/3 inch		
	Pixels - Total	811 x 508		795 x 596
	Pixels - Effective	768 x 494		752 x 582
Scanning	System	Interlace		
	Horizontal Frequency-Internal Mode	15,734 Hz		15,625 Hz
	Horizontal Frequency-Line-lock Mode	15,750 Hz		15,625 Hz
	Vertical Frequency--Internal Mode	5994 Hz		50 Hz
	Vertical Frequency-Line-lock Mode	60 Hz		50 Hz
Min. scene Illumination	Color	0.3 Lux (Sense Up x160 : 0002)		
	B/W	0.06 Lux (Sense Up x160 : 00004)		
Functions	Number of privacy Zone	8		
	Day/Night	Color / BW / AUTO / EXT		
	Motion Detection	Off / On		
	D-Zoom	Off ~ x10		
	High Speed Shutter	Off ~ 1 / 10Ksec		
	Sense Up	Off ~ x128		
	PIP	Off/On		
	BLC	Off/On		
	AGC	Off/On		
	ELC	Off/On(Max. 1/100Ksec)		
	Line Lock	Off/On		
	Camera ID	Off/On		
	White Balance	ATW / AWC / MANUAL		
Resolution	Horizontal	500/530(Color/BW) TV Lines		
	Vertical	350 TV Lines		
Video Output	VBS 10Vp-p	VBS 10Vp-p		
S/N Ratio	S/N Ratio	52dB		
Lens	Lens Drive Type	AI(Video/DC)		
	Mount Type	C / CS		
OSD	OSD	Yes		
Alarm	Output	1		
Environmental Conditions	Operating Temperature	-10° C ~ +50° C		
	Humidity	Less than 90%		
Power	Power Requirement	AC24V(60Hz)±10% DC12V+10%/ -5%	AC220V~240V(50Hz)	AC24V(50Hz)±10% DC12V+10%/ -5%
	Power Consumption	45W		50W
Physical Specification	LED Indicator	Yes		
	Dimensions (WxHxD)-Net	65 x 55 x 130.5 mm		
	Weight-Net	450g		550g
	Loading Quantity(20/40ft)	10560 / 21870		
	Packing	530 x 241 x 182 mm		

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model