Specifications

* SCC-B2091P model is same as SCC-B2391 except for power input (AC230V)

					, ,
		SCC-B2300	SCC-B2391	SCC-B2391P	SCC-B2091P
Camera Type	Color	Color			
Image	Device	Super-HAD CCD			
	Size	1/3 inch			
	Pixels - Total	537 x 505	811 x 508	795 x 596	
	Pixels - Effective	505 x 492	768 x 494	752 x 582	
Scanning	System	Interlace			
	Horizontal Frequency - Internal Mode	15,734 Hz 15,625 Hz			
	Horizontal Frequency - Line-lock Mode	15,750 Hz		15,625 Hz	
	Vertical Frequency - Internal Mode	59.94 Hz		50 Hz	
	Vertical Frequency -Line-lock Mode	60 Hz		50 Hz	
Min. Scene	Color	0.2 Lux 0.3 Lux			
Illumination	B/W	003 Lux 006 Lux			
Functions	Day/Night	AUTO / EXT			
	BLC	On			
	AGC	On			
	ELC	On(Max.1/100Ksec)			
	Line Lock	Off/On			
	White Balance	ATW / MANUAL			
Resolution	Horizontal	400/420(Color/BW) TV Line 540/570(Color/BW) TV Line			
	Vertical	350 TV Lines			
Video Output	VBS 1.0Vp-p	VBS 10Vp-p			
S/N Ratio	S/N Ratio	50 dB			
Lens	Lens Drive Type	AI (Video/DC)			
Environmental	Operating Temperature	-10 ° C ~ +50 ° C			
Conditions	Humidity	Less than 90%			
Power	Power Requirement	AC24V(60Hz) ± 10% DC12V+10%/-5%		AC24V(50Hz) ± 10% DC12V+10%/-5%	AC220V ~ 240V(50Hz)
	Power Consumption	3 W			4 W
Physical	LED Indicator	Yes			
Specification	Dimensions (WxHxD) - Net	68(W) x 55(H) x 128.5(D)mm			
	Weight - Net	450 g 550 g			
	Loading Quantity(20/40ft)	10,560 / 21,870			
	Packing	540 x 241 x 251 mm			
	Tuesding	010 / 21 / 2011			

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model.