## Specifications

		SCC-C4207	SCC-C4307	SCC-C4207P	SCC-C4307P
Camera Type	Color	Color			
Image	Device	Ex-View PS CCD			
	Size	1/4 inch			
	Pixels - Total	811 x 508 795 x 596			
	Pixels - Effective	768 x 494 752 x 582			x 582
Scanning	System	Interlace			
	Horizontal Frequency-Internal Mode	15,734 Hz 15,625 Hz			25 Hz
	Horizontal Frequency-Line-lock Mode	-	15,750 Hz	-	15,625 Hz
	Vertical FrequencyInternal Mode	59.9	4Hz	50	)Hz
	Vertical Frequency-Line-lock Mode	-	60 Hz	-	50 Hz
Min. scene	Color		0.09 Lux(Sense Up x 4, 15 IRE	E, Sense Up x 128 : 0.002 Lux)	
Illumination	B/W	0.009 Lux(Sense Up x 4, 15 IRE, Sense Up x 128 : 0.0002 Lux)			
Functions	Day/Night	Color / BW / Auto / EXT			
	Motion Detection	Off/On			
	Wide Dynamic Range	Off/On			
	D-Zoom	Off ~ x10			
	High Speed Shutter	Off ~ 1/10Ksec			
	Sens Up	Off ~ x160			
	BLC	Off/On			
	AGC			W / HIGH	
	Line Lock	_	Off/On	-	Off/On
	Camera ID	Max 20 Character			
	White Balance	ATW-1 / ATW-2 / AWC / MANUAL			
	Number of Privacy Zone	8 ea			
Resolution	Horizontal	480 TV Lines			
0001041011	Vertical	350 TV Lines			
Video Output	VBS 1.0Vp-p	VBS 1.0Vp-p			
S/N Ratio	S/N Ratio	50dB			
Lens	Focal Length	3.55 ~ 113 mm			
البا	Zoom ratio	32X			
	Aperture Ratio	F1.69(Wide), F4.17(Tele)			
	Viewing Angle-Tele	1:78'(H) x 1:34'(V)			
	Viewing Angle-Tele Viewing Angle-Wide	41° 5′(H) x 43° 01′(V)			
OSD	OSD Viewing Angle-Wide	Yes			
Alarm	Output	1			
Remote Control	RS485	Yes			
Environmental	Operating Temperature	-10 ° C ~ +50 ° C			
Conditions	Humidity	Less than 90%			
Power	Power Requirement		AC24(60Hz)		AC24(50Hz)
OWE	'	DC12V+10%/-5%	DC12V+10%/-5%	DC12V+10%/-5%	DC12V+10%/-5%
	Power Consumption	5.5W	6W	5.5W	6W
	LED Indicator			és	
Physical	Dimensions (WxHxD)-Net	59.5 x 60.5 x 115.7mm	59.5 x 60.5 x 149.9mm	59.5 x 60.5 x 115.7mm	59.5 x 60.5 x 149.9mm
Specification	Weight-Net	390g	515g	390g	515g
	Loading Quantity (20/40ft)	828 / 1692	928 / 1880	828 / 1692	928 / 1880
	Packing	112 x 95 x 170mm	114 x 97 x 205mm	112 x 95 x 170mm	114 x 97 x 205mm