

Specifications

			SHR-2042P	SHR-2042
Operating System			Embedded OS	Embedded OS
Storage Capacity	Internal	Basic	160GB	160GB
		Max. Expansion	250GB x 3	250GB x 3
		CD-RW	for Backup	for Backup
Video	External Inputs	USB HDD	Max. 250GB, 1EA	Max. 250GB, 1EA
		Composite	4Ch	4Ch
		Composite Through	4Ch	4Ch
	Outputs	Composite	2Ch(Main, Spot)	2Ch(Main, Spot)
		S-Video	1Ch	1Ch
		VGA	1Ch	1Ch
	Compression		MPEG4	MPEG4
	Compression Rate	Very High	81KB(352x288), 206KB(720x288)	6.7KB(352x240), 172KB(720x240)
		High	61KB(352x288), 15.7KB(720x288)	5.0KB(352x240), 13.2KB(720x240)
		Standard	48KB(352x288), 121KB(720x288)	3.9KB(352x240), 10.0KB(720x240)
		Low	2.9KB(352x288), 7.8KB(720x288)	2.4KB(352x240), 6.3KB(720x240)
Display Speed(images/sec)		100	120	
Display Resolution		720x576	720x480	
Recording /Search	Recording Mode		Time Lapse	Time Lapse
	Search / PB Mode	Search	Event Alarm/Motion/Video Loss Schedule(Time/Date/Camera)	Event Alarm/Motion/Video Loss Schedule(Time/Date/Camera)
			Event Search(Alarm/Motion/Video Loss), Date/Time Search	Event Search(Alarm/Motion/Video Loss), Date/Time Search
			Go to First/Last Search, Backup Search	Go to First/Last Search, Backup Search
		PB	Play, Stop, Pause, FF, FB, Forward Frame Advance, Reverse Frame Advance	Play, Stop, Pause, FF, FB, Forward Frame Advance, Reverse Frame Advance
Recording Speed(images/sec)		100(352x288), 50(720x288), 25(720x576, 1CH mode only)	120(352x240), 60(720x240), 30(720x480, 1CH mode only)	
Recording Resolution		CIF(352x288), Half D1(720x288), D1(720x576, 1CH mode only)	CIF(352x240), Half D1(720x240), D1(720x480, 1CH mode only)	
Auto Switching			0, 3, 5, 10, 20, 30sec	0, 3, 5, 10, 20, 30 sec
Live Division Screen			Single, Quad, x2 Zoom, Freeze	Single, Quad, x2 Zoom, Freeze
Audio	Inputs		4Ch, RCA	4Ch, RCA
	Outputs		1Ch, RCA	1Ch, RCA
	Compression		ADPCM	ADPCM
	Recording		4Ch	4Ch
Alarm	Inputs		4 Alarm, 1 Alarm Reset	4 Alarm, 1 Alarm Reset
	Outputs		2 Alarm Out	2 Alarm Out
	Pre Alarm		Off, 5, 10, 20, 30sec	Off, 5, 10, 20, 30sec
	Post Alarm		Off, 5, 10, 20, 30sec, 1, 3, 5, 10, 20min	Off, 5, 10, 20, 30sec, 1, 3, 5, 10, 20min
Motion Detection			Area Setting	Area Setting
Network			Ethernet : 10/100 Base T, Static IP, Dynamic IP(DHCP), ADSL(PPPoE)	Ethernet : 10/100 Base T, Static IP, Dynamic IP(DHCP), ADSL(PPPoE)
Backup	USB 2.0		Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)	Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)
Serial I/F(RS-485)			PTZ Device Control, System Key Board	PTZ Device Control, System Key Board
Watermark			Yes	Yes
Multiplex function			Triplex	Triplex
Power Requirements			AC 100~240V, 50/60Hz	AC 100~240V, 50/60Hz
Weight			6.5kg	6.5kg
Dimensions(WxHxD)mm			430 x 88 x 400 mm	430 x 88 x 400 mm
Packing			559 x 517 x 204 mm	559 x 517 x 204 mm

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model