

Specifications

		SHR-2082P	SHR-2082	
Operating System		Embedded OS	Embedded OS	
Storage Capacity	Internal	Basic	160GB	
		Max. Expansion	250GB x 3	
	External	CD-RW	for Backup	
USB HDD		Max. 250GB, 1EA		
Video	Inputs	Composite	8Ch	
		Composite Through	8Ch	
	Outputs	Composite	2Ch(Main, Spot)	
		S-Video	1Ch	
		VGA	1Ch	
	Compression		MPEG4	MPEG4
	Compression Rate	Very High	10.25KB(352x288), 176KB(720x288)	8.5KB(352x240), 146KB(720x240)
		High	7.75KB(352x288), 13.4KB(720x288)	6.4KB(352x240), 11.25KB(720x240)
		Standard	6KB(352x288), 10.25KB(720x288)	4KB(352x240), 8.5KB(720x240)
		Low	3.75KB(352x288), 6.7KB(720x288)	3KB(352x240), 5.4KB(720x240)
Display Speed(images/sec)		200	240	
Display Resolution		720x576	720x480	
Recording /Search	Recording Mode		Time Lapse, Event Alarm/Motion/Video Loss	
	Schedule(Time/Date/Camera)		Schedule(Time/Date/Camera)	
	Search / PB Mode	Search	Calendar Search, Event Search(Alarm/Motion/Video Loss), Date/Time Search, Go to First/Last Search, Backup Search	
		PB	Play, Stop, Pause, FF, FR, Forward Frame Advance	
	Recording Speed(images/sec)		100(352x288), 50(720x288)	120(352x240), 60(720x240)
Recording Resolution		CIF(352x288), Half D1(720x288)	CIF(352x240), Half D1(720x240)	
Auto Switching		0, 3, 5, 10, 20, 30sec	0, 3, 5, 10, 20, 30sec	
Live Division Screen		Single, Division(4, 6, 7, 8, 9), PIP, Sequence, x2 Zoom, Freeze	Single, Division(4, 6, 7, 8, 9), PIP, Sequence, x2 Zoom, Freeze	
Audio	Inputs		4Ch, RCA	
	Outputs		1Ch, RCA	
	Compression		ADPCM	
	Recording		4Ch	
Alarm	Inputs		8 Alarm, 1 Alarm Reset	
	Outputs		4 Alarm Out	
	Pre Alarm		0, 5, 10, 20, 30sec	
	Post Alarm		0, 5, 10, 20, 30sec, 1, 3, 5, 10, 20min	
Motion Detection		Area Setting	Area Setting	
Network		Ethernet : 10/100 Base T, ADSL Static IP	Ethernet : 10/100 Base T, ADSL Static IP	
		ADSL Dynamic IP(PPPoE), Cable Network(Dynamic IP)	ADSL Dynamic IP(PPPoE), Cable Network(Dynamic IP)	
Backup		Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)	Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)	
Serial I/F(RS-485)		PTZ Device Control, System Key Board		
Watermark		Yes	Yes	
Multiplex function		Triplex	Triplex	
Power Requirements		AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	
Weight		78kg	78kg	
Dimensions(WxHxD)mm		430 x 88 x 400 mm	430 x 88 x 400 mm	

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model