

Specifications

		SHR-2162P	SHR-2162
Operating System		Embedded OS	Embedded OS
Storage Capacity	Internal	160GB	160GB
	Max. Expansion	250GB x 3	250GB x 3
		CD-RW for Backup	for Backup
External		USB HDD	1EA (Max. 250 GB)
Video	Inputs	Composite	16Ch
		Composite Through	16Ch
Outputs		Composite	2Ch(Main, Spot)
		S-Video	1Ch
		VGA	1Ch
Compression		MPEG4	MPEG4
Compression Rate	Very High	124KB(352x288), 21KB(720x288)	10.25KB(352x240), 176KB(720x240)
		High	94KB(352x288), 16KB(720x288)
		Standard	725KB(352x288), 12.4KB(720x288)
		Low	4KB(352x288), 8KB(720x288)
Display Speed/Images/sec		400	480
Display Resolution		720 x 576	720 x 480
Recording /Search	Recording Mode		Time Lapse, Event Alarm/Motion/Video Loss, Schedule(Time/Date/Camera)
	Search / PB Mode	Search	Calendar Search, Event Search(Alarm/Motion/Video Loss)
		PB	Data/Time Search, Go to First/Last Search, Backup Search
	Recording Speed/Images/sec		100(352 x 288), 50(720 x 288)
Recording Resolution		CIF(352 x 288), Half D1(720 x 288)	CIF(352 x 240), Half D1(720 x 240)
Auto Switching		0, 3, 5, 10, 20, 30sec	0, 3, 5, 10, 20, 30sec
Live Division Screen		Single, Division(4, 6, 7, 8, 9, 16), PIP, Sequence, Freeze, x2 Zoom	Single, Division(4, 6, 7, 8, 9, 16), PIP, Sequence, Freeze, x2 Zoom
Audio	Inputs		4Ch, RCA
	Outputs		1Ch, RCA
	Compression		ADPCM
	Recording		4Ch
Alarm	Inputs		16 Alarm In
	Outputs		4 Alarm Out, 1 Alarm Reset
	Pre Alarm		0, 5, 10, 20, 30sec
	Post Alarm		0, 5, 10, 20, 30sec, 1, 3, 5, 10, 20min
Motion Detection		Area setting	Area setting
Network		Ethernet : 10/100Base T, ADSL Static IP, ADSL Dynamic IP(PPPoE)	Ethernet : 10/100Base T, ADSL Static IP, ADSL Dynamic IP(PPPoE)
Backup		Cable Network(Dynamic IP)	Cable Network(Dynamic IP)
USB 20		Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)	Front 1, Rear 1 port, External HDD, USB Memory, External CD-RW, DVD-RW(+R Only)
Serial I/F(RS-485)		PTZ Device Control, System Key Board	PTZ Device Control, System Key Board
Watermark		Yes	Yes
Multiplex function		Triplex	Triplex
Power Requirements		AC 100 - 240V, 50/60Hz	AC 100 - 240V, 50/60Hz
Weight		78kg	78kg
Dimensions(WxHxD)mm		430 x 88 x 400 mm	430 x 88 x 400 mm

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model