

Ruggedly Reliable
Best Service in Industry
Software Excellence

ProScript Interface
Extensive SDKs
Supports OmniScript

Application types

- locally-installed
- remote server-based

StaticCap™ sensing
Long lifetime pen
>1 million signatures

2 Year Warranty
30 Day free evaluation[†]
RapidCare replacement[†]

www.scriptel.com

Scriptel® ScripTouch® Slimline 1X5 USB ST1475 ProScript Device Interface



The ScripTouch Slimline 1x5 USB signature pad with ProScript device interface is the first electronic signature pad for under \$100 to feature Scriptel's proven active battery-less tethered pen in a low-profile modern design with a wide, ergonomic palm rest area. The ProScript device interface supports communication between the ST1475 and software applications that have embedded Scriptel SDKs or use the OmniScript™ universal signature integration platform.

Key Features

- Slim design with wide palm rest
- Active battery-less tethered pen
- Durable plastic case construction with heavy-duty cable attachments
- Horizontal snap-in and vertical pen mounts
- Bottom-side rubber feet and mounting holes

Available Software and Integration Support

- Microsoft Word and Excel plugins
- Adobe Acrobat and Reader plugins
- ScripTouch Sign and Save signature image capture application
- Supports OmniScript universal signature integration platform
- Need help with integration? Scriptel's US-based software development team is at your disposal

Scriptel
CORPORATION

2174 Dividend Drive Columbus, Ohio 43228
Telephone - 877.848.6824 Fax - 614.276.7615

[†] if qualified

Ruggedly Reliable
Best Service in Industry
Software Excellence

ProScript Interface
Extensive SDKs
Supports OmniScript

Application types
• Locally-installed
• Remote server-based

StaticCap™ sensing
Long lifetime pen
>1 million signatures

2 Year Warranty
30 Day free evaluation[†]
RapidCare replacement[†]

www.scriptel.com

Scriptel® ScripTouch® Slimline 1X5 USB ST1475 ProScript Device Interface

Specifications

Active Signature Area	1.13" x 4.25" (28.7 x 108.0mm)
Signature Display	Not on signature pad, signature rendered on host
Pen Type	Active battery-less tethered pen
Sensing Technology	Scriptel StaticCap capacitive sensing
Min Signature Resolution	500ppi
Min Signature Sampling Rate	120pps
Product Dimensions	6" x 5.375" x 0.95" (152.4 x 136.5 x 24.1mm)
Data Interface	USB 2.0 (standard A-type connector)
Data Protocol	Scriptel ProScript device interface
Power Supply	USB bus-powered, no separate external power supply needed
Operating Systems	Support available for Windows, Mac OS, Linux
Development Environments	.NET, JavaScript, Java, PHP, WebSockets and others on request
Downloadable Software	ScripTouch Sign and Save, ScripTouch Toolbox, OmniScript universal signature integration platform, Word, Excel and Adobe plugins
Warranty	2 Year

Scriptel[®]
CORPORATION

2174 Dividend Drive Columbus, Ohio 43228
Telephone - 877.848.6824 Fax - 614.276.7615

[†] if qualified