ST1401 Web Signature Pad

Created by Developers for Developers

PATENT PENDING PLATFORM INDEPENDENT SOLUTIONS

- Supports Windows, Mac, and Linux
- Supports Internet Explorer,
 Firefox, Chrome, Safari, and more
- Eliminates Third Party
 Plugins and Controls
- ◆ Scriptel[®] Static Capacitive

 Digitizer

FREE 30 DAY EVALUATION KIT WILL PROVIDE YOU WITH:

- Upfront Evaluation CostSavings
- ♦ Free 30 Day Evaluation
- Direct Developer Support
 from Software Engineers
- ♦ Option to Buy Demo Kit

For more information on any of our products or services please visit us on the Web at:

www.scriptel.com



Supports Windows, Mac, and Linux

By using standard drivers common across all major computer operating systems, the ST1401 Signature Pad does not require any additional software installed to client machines.

Supports Internet Explorer, Firefox, Chrome, Safari, and more
The ST1401 Signature Pad uniquely passes signature data points
in a format friendly way to all major web browsers. We greatly
reduce the amount of testing needed to support the ever
changing browser landscape.

Eliminates 3rd Party Plugin Development

The ST1401 Signature Pad eliminates the need for ActiveX controls or Java Plugins by passing signature data directly to the browser. Coordinate information can be received through a basic script.

Capacitive Glass Technology

Our screen technology is accurate down to the pixel and captures signatures precisely, even with a finger or palm on the screen while signing. The signature quality remains accurate in the midst of scratches and foreign substances.

Specifications

♦ Connection: USB 2.0

♦ Input Sensor: Scriptel® Static Capacitive Glass

• Pen Type: Tethered Active Pen

• Inking Conversion Rate: 150+ Points per Second

◆ **Dimensions:** 4" x 7" x 1.3" (97mm x 152mm x 33mm)

• **Signing Area:** 4.4" x 1.3" (112mm x 33mm)

♦ Warranty: 3 Years Parts and Labor

SERVICES AVAILABLE

Technical Support

Maintenance

Application Support

Hardware Support

Guaranteed Warranty



ST1401 Web Signature Pad

Created by Developers for Developers

| SVSTEM | PERFORMANCE |
|--------|-------------|
| SISIEM | LINIUMANCE |

Input Method Pen

Detection Method StaticCap®

Accuracy 1 pixel

Linearization Factory

Processor Renesas R5F61664

Memory 512KB Flash

RELIABILITY

Surface Withstands most surface contaminants

Liquid Resistance Liquids on screen do not impede performance

Operational 0-50 degrees Celsius

Temperature

Humidity Less than 95%, non-condensing

Life Expectancy 1,000,000 signatures

WARRANTY

3 years

OPERATING SYSTEMS SUPPORTED

Windows, Mac, and Linux

MECHANICAL

| Structure | Glass |
|-----------------|--|
| Glass Thickness | .078" |
| Screen Size | 4.4"x1.3" |
| Sensor | ITO Coated Glass |
| Actuation Force | 45g +/- 5 g |
| Pen Cable Exit | Rear Center |
| USB Cable Exit | Rear Left |
| Cleaning | Water, isopropyl alcohol, or similar non-abrasive cleaners |

CONTROLLER

| Controllers | Scriptel® ASIC |
|-------------|----------------|
| Available | • |

ELECTRONICS

| Communication | USB |
|-------------------|-------------------------|
| Dimensions | 7"x4"x1.3" |
| Connectors | 4-pin, USB TYPE A, male |
| On Board Voltage | 3.3V and 5V |
| Input Voltage | USB 5V |
| Point Speed (PPS) | >150 |

For more information on any of our products or services please visit us on the Web at:

www.scriptel.com

