

# socket. Bluetooth® Cordless Hand Scanner (CHS) Series 7 (V3)

## 1D MODELS

## Lightweight, Pocket-sized, Dependable



The Socket Bluetooth Cordless Hand Scanner (CHS) Series 7 brings industrial-class barcode scanning into a portable, pocket-sized form factor.

## **Designed for Mobility:**

- Small, light, portable
- Wireless with long-range *Bluetooth* connection
- Excellent ergonomics ensure comfortable use over extended periods
- Dependable performance with long battery life
- Easy integration with applications on diverse mobile computing platforms



General Purpose Barcode Scanners	7C	<ul> <li>Smallest, lightest and most affordable version</li> <li>For light-duty scanning (&lt;100 scans per day) up to 20" (51 cm) away</li> <li>Scans barcodes printed on labels or displayed on device screens</li> <li>Recommended for ISBN book scanning for book scouting or library apps</li> </ul>		
	7E	- For light-duty scanning (<100 scans per day) up to 10.5" (27 cm) away - Class 1 laser ideal for average size barcodes - Recommended for ISBN book scanning for book scouting or library apps		
	7M	- For moderate to intensive scanning throughout 8-10 hour work shift - Class 2 laser has longer range for hard-to-reach areas like high shelves - Great for indoor scanning of ISBN or VIN (even scans through windshields)		
Extra Durable Barcode Scanner  Indoors / Outdoors High Performance		- Efficiently scans thousands of barcodes per day, even on reflective surfaces - Best option for scanning VIN indoors and outdoors - even through windshield - Class 2 laser reads 1D linear barcodes, even if small or poorly printed		

#### HARDWARE FEATURES

- Works with Bluetooth enabled PDAs, smartphones, tablets, notebooks and desktop computers:
  - Windows Mobile, 7, Vista, XP
  - Apple iPod touch, iPhone, iPad and Mac OS®
  - Android OS, BlackBerry OS, QNX
- Class 1 Bluetooth 2.1 + EDR provides secure, longrange wireless connection up to 330 ft / 100 m
- Battery Friendly® technology enables extensive battery life on a single charge
- CHS 7P features extra durable exterior casing to withstand multiple 1.5 m (5 ft) drops to concrete
- Easy to use with automatic reconnections
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode for good scans, great for noisy environments where beeps are hard to hear (7P only)
- Allows access to Apple iOS on-screen keyboard
- Supports Bluetooth HID connections for easy setup with no software installation1
- Supports Bluetooth SPP connections for advanced scanner control<sup>2</sup>

### **SOFTWARE FEATURES** (SPP mode only)

- SocketScan™ 10 keyboard wedge software enters scanned data into any application — no custom programming needed
- Socket EZ Pair automates *Bluetooth* setup for maximum ease of use
- Suffix support option to automatically add a carriage return or tab after each scan of data
- Configure beep, LED and vibrate settings
- Enable / disable symbology (barcode type)
- Monitor scanner battery level
- Determine the symbology or length of a barcode
- SocketScan 10 SDK available with optional developer compensation program http://www.socketmobile.com/products/sdk/

<sup>1</sup>HID not supported for BlackBerry OS or iPhone 3G. <sup>2</sup>SPP not supported for iOS, Mac OS or QNX.

CHS Model	<b>7C</b> (v3)	<b>7E</b> (v3)	<b>7M</b> (v3)	<b>7P</b> (v3)			
SKU #	CX2868-1342	CX2858-1294	CX2860-1296	CX2862-1298			
Dimensions	129 x 40.1 x 34.6 mm (5.07 x 1.57 x 1		132 x 45.1 x 37.9 mm (5.2 x 1.77 x 1.49 in.)				
Total Mass	45 g (1.6 oz)	51 g (1.8 oz)	51 g (1.8 oz)	approx. 68 g (2.4 oz)			
Type of Exterior Case	Standard exterior case withstands 1.	concrete	Extra durable to withstand 1.5 m (5 ft) drops to concrete				
Built-in Stylus Tip	Included, designed for Pocket PC or other resistive device touch screens Support for capacitive device screens coming soon.						
Temperature	Operating: +32 to +122°F (0 to +50°C) Storage: -22 to +158°F (-30 to +70°C) Ranges may vary with battery shelf life.						
Relative Humidity	5% to 95% non-condensing						
Ambient Light	Sunlight 9690 lux Artifical 4845 lux Sunlight: 10,000 ft. candles (107,640 lux) Artificial light: 450 ft. candles (4,844 lux)						
Battery Type	Two AAA NiMH rechargeable batteries						
Battery Life	19 hours or 11,000 scans 19 hours or 15,000 scans¹						
Battery Charging Time	With AC adapter: approx. 5 hours (under conditions of 0 to +40°C)						
Barcode Scanner Performance							
Scanner Type	Imager (1D)	Class 1 laser (1D)	Class 2 laser (1D)	Class 2 laser (1D)			
Scans Barcodes on Device Screens							
Scans VIN through windshield	<b>V</b>						
Vibrate Mode for Good Scans			V				
Symbologies Decoded	Same as 7E/M/P plus: UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5						
Scan Repetition Rate	50 scans/sec						
Optical Resolution	5 mil minimum 6 mil minimum 0.004 inch (0.102 mm) mi			code element width			
Print Contrast	Minimum 20%						
Scan Angle	53.3° ± 3° Wide (default): 47° ±3° Narrow: 35° ±3°						
Decode Distance <sup>2</sup>	5.7 to 50.8 cm (2.25 to 20 in.)	3.8 to 114+ cm (1.5 to 45+ inche	es)				
Bluetooth Profile Support	5.7 to 50.8 cm (2.25 to 20 in.)  3.8 to 27 cm (1.5 to 10.5 in.)  3.8 to 114+ cm (1.5 to 45+ inches)  Human Interface Device (HID) and Serial Port Profile (SPP)  Some OS versions or device models support only one profile.						
Bluetooth Protocol	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption, Bluetooth QD ID B0164000						
Bluetooth Frequency	2.4 to 2.4835 GHz ISM band, supports Advanced Frequency Hopping						
Radio Range	Class 1 Bluetooth: Up to 330 ft (100 m), depending on environment						
OS Support							
Apple iOS: iPad, iPhone, iPod touch	<b>√</b>		<b>√</b>	<b>√</b>			
• Mac OS	<b>√</b>	./					
Android OS	<b>√</b>						
BlackBerry OS	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>			
• Windows 7, Vista, XP, Mobile	<b>V</b> ✓	, <u>, , , , , , , , , , , , , , , , , , </u>	· /				
• QNX	./	./					
SocketScan™ 10 Software	Keyboard wedge for Android, Black	Berry, Windows included. SDK so	Id separately, http://www.socketn	nobile.com/products/sdk/			
Included Items	CHS barcode scanner, AAA rechargeable batteries (2), USB AC charger kit, Lanyard/belt clip with retractable tether, Software						
Warranty	Scanner: One year Accessories: 90 days						
SocketCare™ Service Program	Sold separately. SocketCare Plus 2 Year SKU# SC1804-1349 SocketCare Plus 3 Year SKU# SC1805-1350 http://www.socketcare.com/						
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2						
Environmental	RoHS						
EMI/RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC						
EMI/RFI Laser / LED Safety:	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC  IEC 60825-1, EN 60825-1						

<sup>&</sup>lt;sup>1</sup>Based on elapse time of 5 seconds/scan under typical usage conditions. Battery performance may vary depending on vibrate settings and work environment.

<sup>&</sup>lt;sup>2</sup>Depends on symbol size, symbology, label media, W-N ratio, scan angle.



insidesales@socketmobile.com

Worldwide +1-510-933-3000 Toll-Free

+1-800-552-3300 (USA/Canada)

**EMEA** +33 682 719 381 UK +44 (0) 7787 112109 Australia +61 (0) 2 8006 5127 +81 (50) 5806 6286 Japan