



2D/1D Imager Barcode Scanner

# *₩* 30 30 30

# **S740 DATASHEET**

#### **Ergonomic and Elegant**

The SocketScan S740 2D/1D imager barcode scanner with Bluetooth wireless technology scans either 1D or 2D barcodes on paper or screen. It has a lightweight, ergo-nomic structure, and a long-lasting battery to withstand entire work days. The five color options fit most styles and environment needs. The lights for battery, Bluetooth and scanning notifications make the scanner more intuitive to use. Compatible with all ap-plications in previous Socket Mobile barcode scanners, without software changes. This scanner is dressed to impress both consumers and end users in retail and office settings. Ideal for retail POS, field service, inventory management, asset tracking and more. Use our Companion App for easy set up and configuration.

#### Made for **□** iPod **□** iPhone **□** iPad



Certified by Apple<sup>®</sup> for iOS devices (iPad<sup>®</sup>, iPhone<sup>®</sup>, iPod Touch<sup>®</sup>) and compatible with Android and Windows<sup>®</sup>.

#### **Features**

- Bluetooth Wireless Technology Connects easily to a wide range of Bluetooth enabled smartphones, tablets, notebook and desktop computers.
- Scanning Fast 2D & 1D, omni-directional, barcode scanning with highly visible and safe LED aimer.
- LED Aimer Bright, rectangular illumination field with LED dot for precise aiming.
- **Exceptional Ergonomics** Small, lightweight, and fits perfectly in the hand for comfortable use over extended periods.
- User Indicators Intuitive LEDs, beeps, and vibrations let users know battery, Bluetooth connection and scanning status.
- Long-Lasting, Replaceable Battery Power to last over 16 hours.
- Protective Material Made with antimicrobial material for protection against potentially harmful bacteria.
- Color Options Blue, green, red, white and yellow colors enable corporate-branding personalization and is easy to find in busy work environments.
- Auto Scan Mode Presentation Mode (automatic scanning) provides continuous scanning capabilities without pressing the scan button.
- Application Integration Socket Mobile's Capture SDK enables integration in your applications to improve business productivity with fast, efficient and reliable data transfer over Bluetooth wireless technology.






#### SINGLE PACKAGE INCLUDES

(1) SocketScan S740, 2D/1D Barcode Imager


- (1) Charging Cable
- (1) Wrist Strap
- (1) Get Started Insert

The S740 is available in 5 colors:



Blue (SKU# CX3431-1881) Green (SKU# CX3417-1836) Red (SKU# CX3413-1832) Yellow (SKU# CX3415-1834) White (SKU# CX3419-1838)

#### **OPTIONAL ACCESSORIES**



Scanner:	Standard one year limited warranty
Accessories:	90 days
Extended Warranty: (sold separately)	www.socketmobile.com/socketcare

## WARRANTY



Default Barcode Symbologies:	<ul> <li>1D Symbologies: Australia Post, Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO</li> <li>2D Symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417</li> </ul>					
Supported Barcode Symbologies:	<b>1D Symbologies:</b> Australia Post, Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO <b>2D Symbologies:</b> Aztec, Data Matrix, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code					
Scan Angle:	42° (Horizontal) - 28° (Vertical)					
Sensor Resolution:	640 horizontal x 400 vertical pixels					
Print Contrast:	Down to 25%					
Reading Distance:	18       POF417 (10 mis)       9.0         20       Code 39 (5 mis)       6.4         20       Code 39 (5 mis)       6.4         20       Code 39 (5 mis)       6.4         5740       08 Code (20 mis)       1.5         15       08 Code (20 mis)       1.5         15       08 Code (20 mis)       1.5         20       Code 39 (20 mis)       1.5         15       00       1.5         20       Code 39 (20 mis)       1.5         20       0       1.5       2.0         0       1.2.7       2.5.4       38.1       50.8					

4.5 to 49.5 cm (1.5 to 19.5 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle

#### BATTERY

Battery:	2 rechargeable, 2000 mAh (LR6) NiMH (replaceable battery)				
Charge Time:	~6 Hours				
Battery Life - Per Full Charge:	Standby time: over 20 hours Active Scan Time: 70,000 scans within 9 hours based on 2 scans every 1 second 17,000 scans within 19 hours based on 1 scan every 4 seconds				
Note:	Battery life varies depending on ambient temperature, ambient light and age of battery.				
	BLUETOOTH (WIRELESS CONNECTION)				
Bluetooth Radio:	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption				
Bluetooth Range:	Up to 10 m (33 ft.) depending on environment, range limit is usually due to the Host Device (phone, tablet or notebook)				

Bluetooth Profiles: Basic Mode - Human Interface Device (HID)\*, Application Mode - Serial Port Profile (SPP) and Application Mode - MFi-SPP. Some Operating Systems or smartphone/tablet models may support only one profile. \*By default, the scanner is set to Basic Mode (HID).

# SCANNER TYPE

Technology:	2D/1D Barcode Linear Imager
Light Source:	Hyper Red 660 nm (nanometer) LED
Aimer:	610 nm LED

USER ENVIRONMENT

Ambient Light:	From 0 to 100 000 lux. From pitch black to direct sun light
Operating Temperature:	0° to 45° C (32° to 113° F)
Storage Temperature:	-40° to 70° C (-40° to 158° F)
Relative Humidity:	95% at 60° C (140° F) (non-condensing)
Drop Specifications:	4 ft. drop to linoleum

## OPERATING SYSTEM COMPATIBILITY

Android OS - Basic Mode (HID)* & Application Mode (SPP)		Mac OS - Basic Mode (HID)* only				
Apple iOS - Basic Mode (HID)* & Application Mode (MFi-SPP)		Windows OS - 10, 8, and 7 - Basic Mode (HID)* & Application Mode (SPP)				
Compatible with devices supporting Basic Mode (HID)* protocol						
Supported keyboard Lo	anguages - English, French, German and	d Spanish				
*By default the scanne	er is in Basic Mode (HID). No software in	nstallation required.				
Certified by Apple <sup>®</sup> for	iOS devices (iPad®, iPhone®, iPod Touch	<sup>®</sup> ) and compatible with Android	and Windows <sup>®</sup> .			
.00	<b>A</b>			5		
iOS	•		SX (	$\mathbf{\hat{j}}$		
			FION & REGULA			
		CERTIFICA	TION & REGULA	TURT		
Bluetooth SIG:	Declaration ID: D030473 QD ID: 82	009				
Electrical Safety:	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2					
Environmental:	Environmental: RoHS EN 50581					
EMI / RFI:	FCC Part 15 Class C, RSS 210, iCES 00	3. C-Tick. CISPR 22. CE EN550	22. EN55024. TELEC			
	FCC ID: T9J-RN42					
	IC ID: 6514-RN42 Telec: R 201-125799					
LED Safety:	IEC/EN 62471 (EXEMPT GROUP)					
LED Salety.						
F© (				$\mathbf{N}$		
	Canada		WEEE V	ROHS		
			COMMON	USES		
Retail/Point of Sale	Mobile Tracking	Transportation	Hospitality			
Office use	Shipping & Receiving	Gaming				
Healthcare	Field Sales/Service	Banking				
socketmobile.com Toll-Free: +1 800 552 3300 (US	sales@socketmobile A/Canada) Asia Pacific: +1	.com 510 933 3122	EMEA & Russia: +41 6	62 834 0780		
France: +33 970 462 241		9 9401 5299 052		02 034 0700 00 9808 0518		
Latin America: +1 510 933 3153	Switzerland: +4	1 62 834 07 80		(0) 1252 761403 7787 112109		
			+44 /	107 112109		

© 2018 Socket Mobile, Inc. All rights reserved. Socket@, the Socket Mobile logo, SocketScan<sup>®</sup>, DuraScan<sup>®</sup>, Battery Friendly® are registered trademarks or trademarks of Socket Mobile, Inc. Microsoft® is a registered trademark of Microsoft Corporation in the United States and other countries. Apple@, iPad@, iPad Mini@, iPhone@, iPad Touch@, and Mac 105@ are registered trademarks of Apple, Inc., registered in the U.S. and other countries. The Bluetooth® Technology word mark and logos are registered trademarks of Apple, Inc., registered in the U.S. and other countries. The Bluetooth® Technology word mark and logos are registered trademarks of Apple, Inc., registered in the U.S. and other countries.