<u> ଛା</u>ଟିଲା **TSP828**



- Print Labels in Batches or Automatically Peeled and Presented
- Easy Drop-In Roll Loading
- High Speed Output
- Easy and Fully Adjustable Roll Widths from 1.7" to 4.4"
- Barcode Support -1 & 2 Dimensional
- Supports Label, Ticket or Receipt Rolls
- USB, Serial, Parallel, Ethernet or WiFi
- Free Label Software Included



Efficient and Convenient











Small Footprint









Dedicated Direct Thermal

Label Printer with an

Automatic Label Peeler

The TSP828 sets the standard when it comes to desktop label printing. With the TSP828, Star meets the high quality, ease-of-use demands of the desktop thermal label printer market. The TSP828 is perfect for all of your printing applications, from shipping and receiving, to healthcare and retail. The TSP828 can accommodate various label formats and widths. The built-in peeler will speed you through your print jobs in an instant, and the rear exit liner ensures no worries of hassling with waste. Print batch jobs or auto-peel your labels without overlapping thanks to the TSP828's ability to sense when a label is still in the dispenser. When

it's time to replace your labels, just drop them in

and start printing - No need to feed or wind anymore!

All of these features make the TSP828 the only true

The TSP828 packs so much value and perform-

ance into a desktop label printer... You'll wonder

clamshell label printer available.

why anyone would choose another.





TSP828 Specifications

	The Ultimate Label Solution!	
Features	Hardware Ultra Fast (150mm/s) Fully Adjustable Width (45mm to 112mm) Built-in Label Peeler with Rear Liner Exit "Drop-In & Print" Clamshell Design Small Footprint 1 and 2 Dimensional Barcodes Swappable Communication Interfaces Rear Feed Slot Available for Large Label Roll up to 10"	Software Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Configuration / Setup Utility Ethernet / WiFi Interface Setup Utility Bartender Light Label Design Software StarlO SDK
Connectivity Note: Connections in bold are supported; grayed-out connection types may be supported by special request.	9-Pin Serial 25-Pin Serial Parallel USB Powered USB Ethernet WiFi Dual 9-Pin Serial/USB	Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port
Drivers	Windows® XP Vista (32 bit / 64 bit) Windows 7 (32 bit / 64 bit) Server 2008 (32 bit / 64 bit) CE XP Embedded POS for .NET	OPOS™ JavaPOS™ USB Vendor Class Linux™ CUPS Mac OS X CUPS
What's Included	TSP828 Label Printer External Power Supply (PS60A) Installation CD (Printer Driver/ Manuals) Bartender Light Label Design Software CD Setup Sheets Start Up Label Roll Ferrite Core (Parallel, USB, Ethernet Models) Tension Shaft (for Receipt Paper Use)	
Optional Accessories	Automotive 24V Power Supply	
Technical Specifications	Print Method: Direct Thermal Print Speed: 26 Labels Per Minute (150mm/s) Paper Width: 45mm to 112mm Paper Thickness: 0.06 - 0.19mm (Label Paper) 0.06 - 0.15mm (Roll Paper) Paper Diameter: Maximum 110mm Emulation: Star Line Mode, Star Page Mode	Power: 24VDC Resolution: 203 dpi MCBF: 37 Million Lines Dimensions: W=180mm, H=157mm, D=213mm
Warranty	For US and Canada: 3-Year Limited Warranty	
For Further Information	Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105	Web: http://www.starmicronics.com



